

Product data sheet

CONSTRUCTION TYPE

Fully integrated dishwashers	•
60 cm dishwashers	•

DESIGN

Control panel colour	Stainless Steel.
Control panel version	Fully integrated fascia
Control type	Programme selector button
Display	3-digit 7-segment display
Display colour	Yellow

CONVENIENCE

Door closing aid	ComfortClose
Time left display	•
Delay start up to 24 h	•
In-operation indicator light	acoustic
Operating noise dB(A) re 1 pW	44

EFFICIENCY AND SUSTAINABILITY

Hot-water connection	•
Proven hygiene	•
ENERGY STAR® Most Efficient	•

EcoPower technology

-

QUALITY OF RESULTS**Fresh-water dishwasher**

-

Recirculation turbothermic drying

-

WASH PROGRAMS**Automatic**

-

Intensive 75°C

-

QuickIntenseWash

-

Sanitize

-

Rinse & Hold

-

CLEANING OPTIONS**Short**

-

Extra clean

-

Extra dry

-

TECHNICAL DATA**Minimum niche height in mm**

33 3/4 (855)

Appliance width in mm

23 5/8 (598)

Appliance height in mm

33 3/4 (855)

Appliance depth in mm

22 1/2 (570)

Appliance depth with door open in cm

47 1/2 (120.5)

Net weight in kg

100 (45.0)

Total rated load in kW

1.400

Voltage in V	120
Fuse rating in A	15
Number of phases	1
Electrical frequency standard	60
Length of water inlet hose in cm	5 (1.50)
Length of water drain hose in cm	5 (1.50)
Length of power cable in m	4 (1.20)
Minimum niche width in mm	23 5/8 (600)
Niche depth in mm	21 3/4 (550)
Maximum niche width in mm	23 5/8 (600)
Maximum niche height in mm	36 1/4 (920)
Min. front panel weight in kg	4.0
Max. front panel weight in kg	11.0
[retro-fittable by Service to min.]	7.0
[retro-fittable by Service to max.]	14.0

BASKET DESIGN

Cutlery loading	Cutlery tray
Basket design	Comfort
FlexCare cup rack	1

SAFETY

Waterproof system	•
--------------------------	---