

# UP30N



Colour range

Body



Blue grey - BG



Antique white - AW



White - WH



Blue - MB



Stainless steel - SS



Graphite matt - MG



Glossy black - BK



Burgundy red - BU



Emerald green - EG



RAL  
Optional RAL - RA

Finishes

Knobs, handles, frames (optional)



Brass - G



Copper - P



Chrome - C



Burnished - B

Optional solid door version

optional +

Order code: add letter "Q" before the "N" letter

Noblesse frames

optional → p. 138

Available ovens


Electric oven

Primary oven:  
UOV 76 M


Maximum input:  
3.7 kW

Configurations

5 burners



Induction



Electric oven

**UP30NMP**

Brass/Copper/Chrome/Burnished

**UPI304NMP**

Brass/Copper/Chrome/Burnished


Fuel requirements


Natural gas / Liquid propane  
Voltage: 240 Volts  
Amps: 15.4


All electric  
Voltage: 240 Volts  
Amps: 47.5


*\*Insufficient amperage may lower heating performance when multiple functions are being used at the same time*


Consumption


 Bridge induction zone  
Ø 7" 1/4 + Ø 7" 1/4  
1.85 / 2.5 kW + 1.85 kW


 Induction zone  
Ø 5" 3/4  
1.4 / 1.8 kW

 Induction zone  
Ø 7" 1/4  
1.85 / 2.5 kW

 Induction zone  
Ø 8" 11/16  
2.3 / 3.2 kW

 Double ring Dual burner  
25000 btu/h / 900 btu/h

 Big burner  
10500 btu/h / 2000 btu/h

 Small burner  
7000 btu/h / 1400 btu/h

Complements & accessories

Hood

UAG30

Hood

UANB30

Ladle holder panel

AM4-76

Brass/Copper/Chrome/Burnished

Technical drawing & dimensions

