
# GE Zoneline® Cooling and Electric Heat Unit, 230/208 Volt



#### Model# AZ45E12DAB



- Cooling capacity 11,700/11,600 BTU
- Energy efficiency 11.8/11.8 EER
- Dehumidification 3.5 pints/hour
- Indoor fan CFM (high/low) 449/270
- Fresh air vent CFM (fully open high fan) 42
- Quiet operation Baked-on mastic sound barrier, cross flow blower and two DC fan motors create less noise to ensure comfort
- Heat & Freeze Sentinels Keeps the room from overheating or freezing
- Electronic temperature limiting Prevents expensive over-cooling or over-heating of the room
- - Electronic touch controls with LED display
- - R-410A refrigerant
- - SMC base pan
- Simplified structure Easy to maintain and service

FEATURES	
Sensible Heat Ratio	62%
Chassis Type	Slide-In
Control Type	Coverless Backlit White LED Touch Controls
Discharge Grille	2-position
Electronic Micro Computer Control	Yes
Fan Cycle Switch	Yes
Fan Motor	2
Fan Speed Control	Yes
Fan Speed Selections	Hi/Low Cooling; Hi/Low Fan Only; Hi/Low Heating
Filter Type	Rigid Frame; Slide-Out
Heat - Cool	Yes
Louver Style	Reversible
Manual Vent Control	Hidden
Rotary Compressor	Yes
Temperature Limiting	Electronic 7-Step
Vent Control	3-position
Venting Features	Concealed Manual Vent Control; Outdoor Vent Control - 3 Positions; Vent Air Filter
Zoneline Features	"Sleep" Mode; "Smart Fan" Fan Cycle Control; Auto Power Recovery; Automatic Indoor Frost Control; Central Desk Control Compatibility; Freeze Sentinel; Heat Sentinel; LCDI Power Cord (purchased separately); Proportional - Integral ID Airflow; Random Twist/Length Segment Tangential Blower; Remote Thermostat Compatibility; Universal Heaters; Weather Protected Electrical Components
Product Type	Packaged Terminal Air Conditioners (PTAC)
Temperature Range	60 - 85 F

Have more questions? Please contact 1-800-626-2005

## GE Zoneline® Cooling and Electric Heat Unit, 230/208 Volt



#### Model# AZ45E12DAB

### APPROXIMATE DIMENSIONS (HxDxW)

• 16 in x 20 13/16 in x 42 in

### CAPACITY

- Cooling BTUH (MIN) 11500.00 Btu
- Cooling BTUH (MAX) 11600.00 Btu
- Cooling EER (BTUH / Watt) 11.7/11.8
- CFM Indoor Fan High 420
- CFM Indoor Fan Low 290
- Dehumidification (pts./hr.) 3.50
- Vent CFM (high fan at zero ESP) 38

#### WARRANTY

- Parts Warranty Limited 1-year entire appliance;
   Limited 5-year sealed refrigerating system
- Labor Warranty Limited 1-year entire appliance; Limited 5-year sealed refrigerating system
- Warranty Notes See written warranty for full details