

Product data sheet

CONSTRUCTION TYPE

Wall-mounted ventilation hood	•
-------------------------------	---

DESIGN

Colour	Stainless steel
--------	-----------------

OPERATING MODES

Recirculation conversion kit (order separately)	DUW 20
Type of air guide	Can be retrofitted
Active charcoal filter (order separately)	DKF12-900P

USER CONVENIENCE

EasySwitch	•
Operation	EasySwitch
Electronic controls	•
Power levels (excluding booster level)	3
Booster levels	1
Easy-to-clean CleanCover hood liner	•

FILTER SYSTEM

Number of dishwasher-safe stainless steel grease filters (10-ply)	3
---	---

LIGHTING

Number x W	3 x 3 W
Light intensity in Lx	450 lx
Colour temperature in K	3000 Kelvin

FAN

Dual-action fan	•
-----------------	---

VENTED SYSTEM

Air throughput and sound emissions	Values upon request
------------------------------------	---------------------

Air throughput in CFM in Booster	510
SAFETY	
Safety shut-off	•
TECHNICAL DATA	
Max. overall hood height for vented and external in mm	39 5/8 (1005)
Max. overall hood height for recirculation in mm	44 3/4 (1135)
Min. overall hood height for vented and external in mm	27 (685)
Min. overall hood height for recirculation in mm	32 1/8 (815)
Canopy width in mm	35 3/8 (898)
Canopy height in mm	2 1/2 (62)
Canopy depth in mm	19 3/4 (500)
Minimum height above electric cooktops in mm	24 1/8 (610)
Minimum safety distance above gas cooktops (max. 12.6 kW total power, burner ≤ 4.5 kW) in mm	26 (660)
Net weight in kg	56 (25.0)
Length of power cable in m	4 (1.5)
Standard plug fitted	•
Total rated load in kW	0.359
Voltage in V	120
Fuse rating in A	15
Frequency in Hz	60
Number of phases	1
INSTALLATION NOTES	
Vent connection at top	•
Diameter of exhaust duct in mm	6 (150)
Telescopic chimney	•
ACCESSORIES SUPPLIED	
Non-return flap	•