





200 CFM/6.5 SONES @ 0.10" SP. Horizontal 200 CFM/6.5 SONES @ 0.10" SP. Vertical

Dimensions

Overall bottom projection - 183/8" Overall top projection -12" Height - 6" Available widths: 30" & 36"

Hood Body

Stainless Steel: 24 gauge, grade 430 stainless steel.

Painted: 23 gauge cold rolled commercial grade (CRCQ) steel, auto welded, coated with a baked enamel finish.

Motor

Variable speed, single coil, thermally protected, permanently lubricated. Rated 120 volts, 60 hz. Complete with 200°C lead wires.

Lighting

Single 60 watt cook light capacity (bulb not included) complete with night light setting.

<u>Ducting Options</u>


Horizontal ducting: 31/4"x10" (duct adapter and damper included). Vertical ducting: 31/4"x10" (duct adapter and damper included). Vertical ducting: 7" round (duct adapter and damper not included). Ductless: removable front vent (charcoal filter not included).

• Fan Blade


One piece polymeric, electronically balanced blade. 65/8" diameter with 5 paddles.

Electrical connection

Hood top - 7/8" electrical knockout. Hood back - 7/8" electrical knockout.



DS SERIES



Filters

UL rated, class 2 filter. Grease Filter: RF35 - 87/8"x103/8" (included). Charcoal Filter: RF34 (not included). Combo Grease/Charcoal: RF55 (not included).

Available Finishes

White, Biscuit, Almond, Black & Stainless Steel.

EXPANDED PERFORMANCE											
	Static Pressure (inches of w.g.)						Sones	Fan Speed	Power		
Air Flow - CFM	0	0.05	0.1	0.15	0.2	0.25	@ .1 SP	RPM	Watts	Apms	
Vertical Ducting	233	218	200	181	158	132	6.5	2847	91.0	1.5	
Horizontal Ducting	233	218	200	181	158	132	6.5	2847	91.0	1.5	

PROJECT							ARCHITECT			
LOCATION							ENGINEER			
CONTRACTOR							SUBMITTED BY DATE			
FAN NUMBER	MODEL NUMBER	СҒМ	IN W.C.	RPM	WATTS	AMPS	SONES	QTY	OPTIONAL EQUIPMENT & REMARKS	





U.S.: 820 Lincoln Avenue West Chester, Pennsylvania 19380-4466 Tel: (610) 692-7400 • 877-304-3785

Fax: (610) 696-8048

Canada: 8 Edvac Drive Brampton, Ontario L6S 5P2 Tel: (905) 456-2033 • 800-250-8767

Fax: (905) 456-1015

Specifications subject to change without notice. Updated 9-12