

24" BEVERAGE COLUMN WITH STAINLESS GLASS DOOR

TR-24BEV-R/L-SG-A

TR-24BEV-R-SG-A (Right hinged)

TR-24BEV-L-SG-A (Left hinged)

FEATURES

- Environmentally friendly, R600a hydrocarbon refrigerant that improves performance and efficiency while ensuring quiet operation.
- Balanced, forced-air refrigeration system enables proper airflow and even temperature throughout to keep food fresh.
- Industry exclusive, 300-series stainless steel interior and exterior.
- All stainless steel, beautifully crafted proud hinges pass True's rigorous one million door opening test.
- Beautifully crafted solid stainless steel door with 120° stayopen feature and ergonomically designed, robust, tubular handle.
- Commercially inspired lift-up grill on top of the unit with toe kick that complements the look of True's undercounter units.
- Ramp-up, showcase interior LED lighting provides amazing illumination throughout.
- Low-E, double pane, UV tinted glass.
- Intuitive True Precision® Control and readout provides digital accuracy and easy operation.
- Shelving to accommodate a variety of bottle shapes and sizes.
- Optional Lock available must be ordered from factory.
- Complies with NSF/ANSI Standard 7 for packaged food product.

ORGANIZATION

- 3 adjustable/removable electropolished stainless steel wire shelves.
- 1 fixed electropolished stainless steel wire shelf.
- 2 full-extension, soft-close wine racks.
- 1 pull-out stainless steel wire wine bin.

BUILD YOUR TRUE

Customize your True with a variety of finish and hardware options at **true-residential.com**.

CUSTOMIZATION




SPECIFICATIONS

Dimensions* (w x h x d)	24" x 84" x 24"
Cutout Dimensions (w x h x d) Flush Opening Standard Opening	24¼" x 84¼" x 26" 23½" x 83¾" x 24"
Capacity (cu. ft.)	15.4
Temperature Range	33°F – 42°F
Weight (lbs.)	455
Voltage	115/60/1 115/60/1 NEMA-5-15R
Amps	1.0
Annual Energy Consumption (kwh)	310
Power Cord Length (ft.)	10
Energy Star Rated	No

*Dimensions may vary +/- $\frac{1}{8}$ "



TR-24BEV-R/L-SG-A



OPENING DIMENSIONS

FLUSH OPENING

WIDTH	HEIGHT	DEPTH
• • • • • • • • • • • •		• • • • • • • • • • • •
241/4"	84 1/4"	26"

STANDARD OPENING*

WIDTH	HEIGHT	DEPTH
23½"	83¾"	24"

^{*}Standard Opening dimensions apply to models produced after April 2024. Please consult factory for clarification / questions.

ELECTRICAL AREA 84 1/4"[2140mm] ТОР FRONT 23 1/2" [597mm] STANDARD INSTALL

MODEL OPTIONS

MODEL	FINISH
TR-24BEV-R-SG-A	Stainless glass door right-hinged
TR-24BEV-L-SG-A	Stainless glass door left-hinged

ACCESSORIES (OPTIONAL)

Joining kit	
Side panel(s)	
Electropolished stainless steel wire shelf	
Full size anti-condensation pad	
Optional Lock — must be ordered from factory.	

WARRANTY

- 3 year full (parts & labor)
- 6 year sealed system (parts & labor)





• 7–12 year (parts only – sealed system on registered products)