

FAD301NWD

Available Colors : White

Version : 06/20

Dehumidifier

Small Room 30 Pint Capacity Dehumidifier



Product Specifications

Dehumidifier

Air CFM (High)	106
Bucket Full Indication	Yes
Bucket Style	Front Pull Out
Charge - ozs	5.64
Container Capacity - Pints	12
Continuous Drain Operation	Yes
Digital Humidity Readout	No
Fan Speed - Fan - General	1
Filter Access	Bottom Slide-Out
Filter Check	No
Filter Type	Easy-to-Clean Washable Filter
Low Temperature Operation	Yes
Motor RPM (High)	1330
Motor RPM (Low)	1150
Noise Level dB (High)	53
Relative Humidity Range Manual	35%-85%

Electrical Specifications

Amps (Cool)	3.4
Horsepower (Cool)	0.43
Plug Type	5-15P
Power Cord Length	6' (6-1/2')
Voltage Rating	115V 60Hz
Watts (Cool)	320

Controls

Auto Shut-Off	Yes
Control Location	Top Center
Control Type	Mechanical Dial

Certifications & Approvals

CSA Listed	No
ETL Listed	No
NSF® Certified	No
Safety Certification	UL/CUL
UL Listed	Yes

Dimensions: Exterior

Depth	19-13/16"
Height	14-9/16"
Width	11-9/16"

Performance

Dehumidification -Pints/Day	30
Dehumidification-Liters/Day	14
EEV (Liters per kW-hour)	1.85

General Specifications

PROP 65 Label	Yes
Reconditioned	No
Refrigerant	R410a
Warranty	1 Year Full/5 Year Sealed System

Note: For planning purposes only. Always consult local and national electric, gas and plumbing codes. Refer to Product Installation Guide for detailed installation instructions on the web at [frigidaire.com / frigidaire.ca](http://frigidaire.com/frigidaire.ca). Specifications subject to change. Accessories information available on the web at frigidaire.com / frigidaire.ca