SUMMIT

SEH4636SSADA



29.5" x 35.44" x 19.69" (H x W x D)

36" wide ADA-compliant European-style convertible wallmounted range hood in stainless steel with remote wall switch

Highlights:

ADA-compliant design allows you to control the hood from a wall light switch for easier accessibility

36" wide wall-mounted range hood

Versatile design for ducted or recirculating operation with a set of carbon filters included

Product Features:

| 36" wide wall-mounted range hood | European style range hood designed to bring effective ventilation over 36" wide cooking surfaces |
|--|--|
| ADA-compliant design | Control panel comes on a remote terminal block to be installed according to ADA compliant guidelines for improved accessibility (some assembly required) |
| Convertible design with no additional purchase necessary | Can be used for ducted venting to the outside or recirculating ventilation where no external venting is possible |
| Charcoal filter set included | Two round carbon filters attach to the blower to absorb grease and odors when using the hood in recirculating mode |
| Powerful ventilation | 400 CFM blower to effectively remove smoke and cooking odors from your kitchen |
| Cord included | Pre-installed power cord with 3-prong plug for 115V outlets |
| LED lighting (bulbs included) | Includes two pre-installed LED bulbs to illuminate your cooking surface |
| Adjustable height | Includes a telescoping chimney extender that allows you to adjust the overall height between 25 1/4" to 37" |
| Stainless steel finish | Durable construction in an attractive style with a horizontal grain |
| | |

SUMMIT APPLIANCE DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified 770 Garrison Avenue Bronx, NY 10474 USA TEL 718-893-3900 FAX 844-478-8799

info@summitappliance.com



SUMMIT

SEH4636SSADA Specifications:

| Width35.Depth19. | 9.5" (75 cm) 44" (90 cm) 69" (50 cm) iinless Steel ETL |
|------------------------|--|
| Depth 19. | .69" (50 cm) iinless Steel |
| · · · | inless Steel |
| Door Sta | |
| | ETL |
| US Electrical Safety | |
| Amps | 2.6 |
| Voltage/Frequency 115 | V AC/60 Hz |
| Weight 55.0 | lbs. (25 kg) |
| Shipping Weight 58.0 | lbs. (26 kg) |
| Parts & Labor Warranty | 1 Year |
| UPC 761 | 101086842 |
| Range Hood | |
| Installation W | all-Mounted |
| Venting | Convertible |
| Controls F | Push Button |
| Light | Yes |
| Number of Lights | 2 |
| Light Type | LED |
| Number of Fan Speeds | 3 |
| Maximum Air Movement | 400.0 CFM |
| Sone Rating | 10 |
| Minimum Height 15. | .75" (40 cm) |
| Maximum Height 29 | 9.5" (75 cm) |
| Duct Shape | 6" Round |

2 Charcoal Filters Included for Recirculating Use



