BRSAN[®] Elite

Broan Elite brings you Spire, an exciting new shape in a pro-style hood. It's high efficiency ensures energy savings while you enjoy pro-style performance.

SIZE	STAINLESS	GREASE FILTERS (replacement)	NON-DUCTED FILTERS				
30-in.	SPE130SS	HPFA424 (Type "B5")	HPF24 (Type "Xb")				
36-in.	SPE136SS	HPFA430 (Type "C5")	HPF30 (Type "Xc")				

	Size	Damper	Sones			CFM			
Duct Orientation			Normal	Medium*	High	Normal	Medium*	High 0.25 in. w.g.	High 0.1 in. w.g.
Vertical - Rectangular	3¼ in. x 10 in.	Included	<0.3*	3.0	8.0*	120*	270	410*	460*
Horizontal - Rectangular	3¼ in. x 10 in.	Included	<0.3*	3.0	7.5*	120*	290	470*	510*
Vertical - Rectangular	3¼ in. x 14 in.	Included	<0.3	3.0	8.0	150	300	470	520
Horizontal - Rectangular	3¼ in. x 14 in.	Included	<0.3	3.0	7.5	140	340	550	590
Round - Vertical	7 in.	Sold Separately	<0.3	3.0	8.0	140	280	415	470

FEATURES								
Max. Blower Airflow	650 CFM							
Control type	3-speed Capacitive Touch							
Delay off	no							
Filter Clean Reminder	yes							
Heat Sentry™	no							
ADA Capable	yes							
Lighting	2-level ENERGY STAR [®] LED (included)							
Grease Filters	Hybrid Baffle (Oty. 2)							
Installation Hardware	EZ1 Brackets							
ENERGY STAR®	yes (no if installed non-ducted)							
Recirculation	Non-ducted filters sold separately							
3¼ in. x 10 in. Damper/ Duct Connector	included							
AC INPUT								
120V, 60 Hz - 1.9 AMF	°S							
OPTIONAL ACCESSO								
7-in. Round Damper	BP87Q							
ADA Wiring Kit	HAWRK3							
Make-up Air Damper	MD6TU, MD8TU or MD10TU							
MOUNTING HEIGHT								
24 in. to 30 in. from coo	oktop to bottom of hood							
LIMITED WARRANTY								
1-year								
3-year (LED modules only)								
(See installation manual for full warranty text.)								
FOR INDOOR USE ONLY								
Vertical High Speed, Horizontal High Speed, 1.0 7-in. round with 3% in. x 10 in. damper Vertical High Speed, Vertical High Speed, Vertical High Speed, with 3% in. x 10 in. damper with 3% in. x 14 in. damper								
0.8								
× ·	with 3¼ in. x 14 in. damper							
0.0 a.n								
tic pressure (in, w.g.)								





HVI-2100 CERTIFIED RATINGS comply with new testing technologies and procedures prescribed by the Home Ventilating Institute, for off-the-shelf products, as they are available to consumers. Product performance is rated at 0.1 in. state pressure, based on tests conducted in AMCA's state-of-the-art test laboratory. Sones are a measure of humanly-perceived loudness, based on laboratory measurements. * Where noted performance rating is not HVI certified but was established in accordance with HVI Standardized test procedure

Broan-NuTone LLC

Static p

0

100

200

300

400

Airflow (cfm)

SERIES

SPE1

SPECIFICATION SHEET

CERTIFIED ENERGY STAR 926 West State Street, Hartford, WI 53027

00

500

600

700

| 1 800-558-1711 | www.Broan-NuTone.com

99046189B

SPIRE

Under-Cabinet