

DW8610





Product family Dishwashers

24" Width 86 cm Commercial height

Installation Fully-integrated built-in

N° baskets 3, Flexi **Engine** Inverter

EAN code 8017709354794



Programs









Number of programs 10 Washing temperatures 30, 40, 50, 65, 75 °F

Automatic Yes Intense Yes Self Clean Yes **Delicates** Yes Normal Yes Rinse Yes Eco express Yes

Express 60' Yes Pots & Pans Yes

Options









Dry Assist+ option Delay start

FlexiZone half-load option

Yes Up to 24 hours

Yes

Gray

Intensive washing zone option

Special programs option Yes

Baskets



Basket color

Central fixed racks Upper basket On 3 levels

Upper basket height

adjustment

Largest loadable dish in 19,0 inches

upper basket

Lower basket

Fixed racks

Lower basket with anti- Yes

drip inserts Colour Inner

Sage Leaf

Components

Cutlery basket Yes



Technical Features

ORBITAL SYSTEM







Width 23 9/16 " Depth 21 5/8 "

Display type LED display (3 digits)

Height 33 3/4 "

Display Delay start, Program

progress indicator Writings in English

Program symbols Writin
On/off indicator Yes

Rinse aid indicator Light

End-of-cycle indicator Acoustic signal

Washing system Orbital
Third spray arm Single
Turbidity sensor Yes

Aquatest

Flood protection system Single Aquastop

Max water hardness

Drying system

100°fH;58°dH

Natural condenser drying,

with Dry Assist + automatic door opening system at the

end of the cycle

Tub materialStainless steelFilterStainless steel

Hinges Self-balancing, Sliding,

FLEXIFIT

4.4 - 24.3 lbs

50 - 215 mm

Min. and max. frontal

panel weight

Min. and max plinth

height

Adjustable feet 2 3/4", from 33 7/8" to 36

5/8" Yes

Yes

1186

Additional gaskets

Back cover

Depth of dishwasher

with open door (mm)

Top cover Metal sheet

Electrical Connection

Plug (B) NEMA 5-15P

Connected power 1100 W
Current 13 A
Voltage 115 V

Frequency (Hz)
Connection type
Power supply cable

length

60 Hz

Single-phase

140 "



Compatible Accessories



KIT86CX-1

Door kit, stainless steel, Canali handle, fully integrated dishwasher h.86 cm Compatible with models with Flexifit and fixed fulcrum hinges.



KIT86PORTWH-1



KIT86PORTAN-1



KIT86PORTX-1

KITFLEXI






KITPL60B

Toekick Kit in White colour with adjustable height and deepness. Can be installed over all the fully integrated and underbench models with variable fulcrum or flexifit hinges.

KITPL60X



KITPL60N







Kit extension for dishwasher and washing machine: length mt. 2

Toekick Kit in Stainless Steel with adjustable height and deepness. Can be fitted over all the fully integrated and underbench models with variable fulcrum or flexifit hinges.



Symbols glossary



Acquastop: Some Smeg dishwashers are equipped with a simple Acquastop: float sensor in the bottom which is necesary to prevent an accidental leakage of water inside the appliance.



Aquatest measures the clarity of the water during an auto program, and automatically ensures the minimum consumption of water and energy.



Anti-drip: Some models of dishwashers are equipped with special polymer nozzles anti-drip, that improve the process of drying.



COMM_HEIGHT_86_72dpi



Delay Timer: The delay timer can postpone the start of the program by up to 24 hours.



Models with new Flexi Fit hinges are able to be installed in kitchens with a plinth of just 5cms. With this new hinge design, the panel has a sliding movement from the bottom to the top, avoiding any possible interference of the panel with the plinth.



FlexiZone: The ½ load flexizone allows you to wash a reduced load saving energy, water and time and there are no restrictions on where the items are placed.



Inverter technology: The evolution of Smeg's driers towards more intelligent and environmentally sustainable models has led to the choice of using Inverter technology with heat pumps, which reduces significantly energy consumption.



Noise Level: Excellent insulation and special devices keep noise to a minimum.



Orbital wash system distributes water evenly throughout the 60cm dishwasher cavity, directing water with precision to ensure an excellent wash.



Auto 45°- 65°: The auto programme regulates the length of a cycle depending on the need for a pre-wash and the number of rinses required.



Delicate: Delicate washing program is designed for delicate dishes which are not heavily soiled.



PRG_RINSE_72dpi



Ultraclean: The Ultraclean option performs a final rinse at a high temperature of 70°c eliminating virtually all bacteria.



The symbols show the number of plate settings of the dishwasher.



System WaterSave ensures the best washing results with minimal water consumption depending on the model of dishwasher.



•••





The Dry Assist + option, in addition to saving energy, ensures perfect drying of the dishes by opening the door automatically at the end of the wash c

(ŝ} ...



Benefit (TT)

Orbital Wash System

Even water distribution, deep cleaning and low noise thanks to the dual rotating spray arms

Orbital washing system, which, thanks to its double arm, its 7 water exit points and thanks to overlapping and simultaneous rotations and 40 rotations per minute, allows ample coverage of the tank area, thus guaranteeing optimal results in any basket-loading configuration.

Flexifit hinge system

Smooth-running door for optimal integration into the kitchen deisgn

The height of the plinth can vary from 5 cm to 21.5 cm, allowing it to fit perfectly into the cabinet. Thanks to this solution, the dishwasher blends harmoniously into its surroundings, with the door and plinth perfectly aligned with the other kitchen furniture.

DryAssist+

The Dry Assist+ system of automatic door opening at the end of the cycle ensures fast and energy-efficient drying