## SUMMIT

# BIM24OSBase34



33.63" x 15.13" x 20.63" (H x W x D)

Outdoor icemaker for built-in use, in complete stainless steel with towel bar handle and lower base storage cabinet

#### **Highlights:**

U.L. approved for outdoor use, with three levels of weatherproofing in design

Complete construction in durable 304 grade stainless steel

Produces up to 10 lbs. of crescent-shaped ice in a day cycle

#### **Product Features:**

U.L. approved for outdoor use	Weatherproof design rated safe for outdoor operation	
Built-in capable	Make the best use of space by installing your appliance under the counter and flush with other cabinets	
Fully finished cabinet	Allows the unit to be used freestanding	
Complete 304 grade stainless steel construction	Durable exterior with lasting elegance	
Professional towel bar handle	A curved stainless steel handle provides generous room for a comfortable grip	
Insulated storage bin	Ice maintains solid crescent shape longer in cold storage bin	
Sealed back	No exposed electrical components	
Storage base	Stainless steel base includes drawer	
100% CFC free	Environmentally friendly design without ozone-damaging chemicals	







### **BIM24OSBase34 Specifications:**

Overview		
Height of Cabinet	33.25" (84 cm)	
Height to Hinge Cap	33.63" (85 cm)	
Width	15.13" (38 cm)	
Depth	20.63" (52 cm)	
Depth with Handle	23.13" (59 cm)	
Depth with door at 90°	34.25" (87 cm)	
Capacity	1.0 cu.ft. (28 L)	
Defrost Type	Manual	
Door	Stainless Steel	
Cabinet	Stainless Steel	
US Electrical Safety	UL	
Canadian Electrical Safety	ULC	
Amps	1.0	
Voltage/Frequency	115 V AC/60 Hz	
Weight	105.0 lbs. (48 kg)	
Shipping Weight	110.0 lbs. (50 kg)	
Parts & Labor Warranty	1 Year	
Compressor Warranty	5 Years	
Icemaker		
Door Swing	RHD	
Reversible	No	
Daily Ice Production	12.0 lbs. (5 kg)	
Ice Storage Capacity	12.0 lbs. (5 kg)	
Ice Shape	Crescent	
Number of Ice Cube Sizes	1	
Refrigerant Type	R134a	
Refrigerant Amount	2.4 oz.	
Interior Height	11.75" (30 cm)	
Interior Width	10.0" (25 cm)	
Interior Depth	13.0" (33 cm)	
Level Legs	4	





