

# **GAS COOKTOP**



# SIGNATURE FEATURES



#### MIN-2-MAX® GAS BURNER

Designed with a dual-flame sealed burner, this cooktop offers the widest range of BTU performance in the industry for the utmost versatility — from a roaring 20,000-BTU boil to a 1,100-BTU simmer.



# PROFESSIONAL-GRADE CONTROL KNOBS

Professional-grade control knobs are designed to provide you with pinpoint precision control.



#### **DEEP-WELL DESIGN**

Keeps spills contained for easy cleanup and lowers the cooking surface to countertop-level, which makes moving oversized pots and pans onto and off of the cooking surface much easier.



# **CONTINUOUS GRATES**

Designed for cooking multiple dishes at varying temperatures on a single cooktop. These grates allow easy movement of even the heaviest pots and pans from burner to burner — without lifting.

# EW30GC60PS

#### PRODUCT DIMENSIONS

Width 30"
Depth 21-3/4"
Height (Extreme Bottom to Underside of Cooktop) 4-1/4"

#### **MORE EASY-TO-USE FEATURES**

#### **SEALED BURNERS**

## **ELECTRIC PILOTLESS IGNITION**

#### **PLATINUM STAR® LIMITED WARRANTY**

Our exclusive limited warranty that includes a 3-year coverage on parts and one year on labor without charge.1

#### PERFECT OVER A WALL OVEN

Mounts above a single wall oven for additional installation options.

#### **DISHWASHER-SAFE GRATES**

For easy cleanup.

#### **A.D.A. COMPLIANT**

When properly installed, this model is A.D.A.-qualified based on the United States Access Board's A.D.A./A.B.A. Accessibility Guidelines and the Department of Justice's 2010 A.D.A. Standards for Accessible Design.

Available in:



Stainless


BURNER	BTU
Min-2-Max® Dual-Flame Sealed Burner	20,000 - 1,100
Sealed Power Burner	12,000
Sealed Precision Burner	9,500
Sealed Precision Burner	7,500
Sealed Precision Burner	5,000 - 750

Eligibility based on product registration with Electrolux North America within 60 days of purchase. Products must have been purchased on or after July 1, 2013. Coverage includes material parts for 3 years and labor for 1 year.



FEATURES	
Deep-Well Formed Cooktop	Yes
Professional-Grade Burner Controls	Yes
Continuous Grates	Yes
Min-2-Max® Dual Flame Sealed Burner – 20,000 - 1,100 BTU	1
Sealed Power Burner – 12,000 BTU	1
Sealed Precision Burner – 9,500 BTU	1
Sealed Precision Burner – 7,500 BTU	1
Sealed Precision Burner – 5,000 - 750 BTU	1
Linear Flow Burner Valves	Yes
Electric Pilotless Ignition	Yes
A.D.A. Compliant*	Yes
ACCESSORIES	
Granite Countertop Installation Kit – PN# 903103-9010	Optional
Grill /Griddle – PN# 318251614	Mail-In Card
LP Gas Conversion Kit	Included
SPECIFICATIONS	
Color –	
Stainless Steel	S
Gas/Power Supply Connection Location	Right Bottom Rear
Voltage Rating	120V/60 Hz/15A
Connected Load (kW Rating) @120 Volts‡	.12
Electrical Cable	Yes
Approved for Single Oven Combination Installation**	Yes
Shipping Weight (Approx.)	59
*When properly installed, this model is A.D.Aqualified based on the United States Ac Accessibility Guidelines and the Department of Justice's 2010 A.D.A. Standards for A	cess Board's A.D.A./A.B.A. ccessible Design.
For use on adequately wired 120V, dedicated circuit having 2-wire service with a sep. Appliance must be grounded for safe operation.	
NOTE: Always consult local and national electric and gas codes. Refer to Product Insta for detailed installation instructions on the web at electroluxappliances.com.	allation Guide
Specifications subject to change.	






Width	30"
Depth	21-3/4"
Height (Extreme Bottom to Underside of Cooktop)	4-1/4"









#### 30" Gas Cooktop Specifications

- Product Weight 47 Lbs.
- Voltage Rating –120V/60Hz/15 Amps
- Connected Load (kW Rating) @120 Volts = .12kW (For use on adequately wired 120V, dedicated circuit having 2-wire service with a separate ground wire. Appliance must be grounded for safe operation.)
- Amps @120 Volts = 1.0 Amps
- · Always consult local and national electric and gas codes.
- Recommended location for grounded 120V outlet is on rear wall in an 8" wide by 10" high area, positioned 22" above floor surface and 4" from right side of cooktop centerline. Access to underside of cooktop and junction box must be provided for inspection and service.
- · Cooktop ships with 3/4" factory regulator.
- LP Gas conversion kit supplied.
- Overhead cabinetry should not exceed a 13" maximum depth.
- Allow 30" minimum clearance between top of cooktop and bottom of unprotected wood or metal overhead cabinetry.
- Absolute minimum horizontal distance between overhead cabinets installed to either side of appliance must be no less than 30".
- Allow 24" minimum clearance when bottom of wood or metal overhead cabinet is protected by not less than 1/8" flame-retardant millboard covered with not less than No. 28 MSG sheet steel, 0.015" stainless steel, 0.024" aluminum or 0.020" copper.

- Allow 2-1/2" minimum distance between rear edge of cutout and nearest combustible surface above countertop.
- Allow 9" minimum clearance from edge of cooktop to nearest combustible wall on either side of unit.
- Installation of drawers beneath cooktop requires minimum 6-1/2" clearance beneath countertop surface and assured clearance for gas and electrical connections.
- To reduce risk of fire when using overhead cabinetry, install range hood that projects horizontally a recommended minimum of 5" beyond bottom of cabinets.
- Gas Cooktop model EW30GC60P is approved to be used over any Electrolux Electric Single Wall Oven. (Refer to Gas Cooktop Installation Over 30"/27" Electric Single Wall Oven Specifications page on web.)

Note: For planning purposes only. Refer to Product Installation Guide on the web at electroluxappliances.com for detailed instructions.

## **Optional Accessories**

• Granite Countertop Installation Kit – PN# 903103-9010



