



## KPH-800 PENDANT HOUSING



Designed exclusively to easily fit either the Klipsch IC-800-T or IC-SW-8T2 In-Ceiling 70/100 Volt Commercial speaker, the KPH-800 now brings the benefits of efficiency and sonic clarity of the Klipsch IC speaker series to an aesthetic, suspended pendant design perfect for distributed sound in higherceiling structures.

PACKAGE CONTENTS

One pendant housing

One 9.5' (2.5m) drop cable attached to three balance cables, each with S-hooks

One Fast Link cable joiner

SPECIFICALLYDESIGNEDFORTheKlipschIC-800-T or IC-SW-8T2 UL certified 70 Volt speakers with integrated backcans

ENCLOSURE
1.5mm Aluminum housing

## SUSPENSION/MOUNTING

Threemountingpoints for balance cables that converge to a single point for drop cable; safety cable attachment (cable not included) on Klipsch IC speaker backcan.

## PENDANT DIMENSIONS

Diameter at base: 16.8" (42.7cm) Flange diameter: 12.5" (31.8cm) Height: 13.7" (34.8cm)

PENDANT NET WEIGHT Approximately 2.2 lbs (1kg) (without speaker/cables)

COLORS White, Paintable

SHIPPING Q3 2016

