



A no-compromise loudspeaker and amplification solution for extreme home theater installations.







M5500IW



M5500IWNCE

ON-WALL OR IN-WALL

As the front, side and rear channels are all complimented by dedicated, extruded, aluminum enclosures, you can be confident the sound will remain consistent whether you choose the on-wall or in-wall installation option. The aesthetic choice is completely up to you. Display them proudly or hide them away. Our desire is to allow you the option of blending them seamlessly into your décor.





SPECIFICATIONS

MODEL	M5500OW	M5500IW	M5500IWNCE
PART	M5500OW	M5500IW	Front LCR In-Wall Speaker Enclosure
Woofer	Dual 8" Coated Paper Cone	Dual 8" Coated Paper Cone	
Midrange	Dual 5" Coated Paper Cone	Dual 5" Coated Paper Cone	
Tweeter	1" Titanium Horn loaded	1" Titanium Horn loaded	
Frequency Response	65Hz – 20kHz	65Hz – 20kHz	
Power RMS	150 Watts	150 Watts	
Power Peak	300 Watts	300 Watts	
Impedance	4 ohm	4 ohm	
Dimensions	44 3/32" x 13" x 4 1/4" (1120 x 330 x 108 mm)	32 ¹ ½6" x 10 ¾" x 3 ½" (830 x 276 x 102 mm)	44 $\%$ 2" x 13" x 3 15 16" (1120 x 330 x 100 mm)
Cutout Dimensions		31 ¹ / ₁₆ " x 9 ¹ / ₃ 16" (804 x 250 mm)	
Mounting Depth	5 ¼" (133 mm)	3 ½" (88 mm)	3 ½" (88 mm)



