

SPECIFICATIONS

INPUTS

Inputs: 5 RCA Unbalanced, 5 XLR Balanced
Input Sensitivity: 1.42 Vrms for full output
Maximum Input Voltage: 2.7 Vrms
Input Impedance: 100 k Ω

OUTPUTS

Amplifier Channels: 5
Power Output (8 Ω): 230 watts per channel
Power Output (4 Ω): 300 watts per channel
Power Output (8 Ω Bridged Mono): 600 watts
Minimum Speaker Load: 4 Ω

PERFORMANCE

Damping Factor: >450
Total Harmonic Distortion: 0.04% (230 watts @ 8 ohms 20 Hz-20 kHz)
Signal to Noise: >102dB, A-wtd ref Full Output
Frequency Response: 10 Hz -20 kHz, ± 1 dB

CONTROL

Remote Power Trigger: +12 VDC or Dry Contact Closure

GENERAL

Power Consumption (Standby): < 2W
Power Consumption (Idle): 38W
Power Consumption (loud listening level): 263W
Power Consumption (maximum): 1500W
BTU/Hour Output (Standby): 5.6 BTU/hr
BTU/Hour Output (Idle): 129 BTU/hr
BTU/Hour Output (1/8th power, loud listening level): 313 BTU/hr
BTU/Hour Output (maximum): 1791 BTU/hr
Protection: clipping, short circuit, thermal, DC offset

WEIGHTS & DIMENSIONS

Dimensions: 17"W x 16.5"D x 5.25"H (3U)
Weight: 41.0 lbs (18.6 kg)

IN THE BOX: Pantages G4, Power Cord, Manual, Warranty