

# 1215R • 15" Solid Door Refrigerator • 1000 Series







INTEGRATED SOLID



BLACK SOLID

# **FEATURES & BENEFITS**

# PERFORMANCE

- Volume of 2.9 cu ft holds up to 57 bottles (12 oz) or 92 cans (12 oz)
- Digital Touch Pad Control is conveniently located on upper face of unit
- Temperature range: 34°F 45°F

# INTERIOR/EXTERIOR

- White interior is illuminated with LED lighting
- Three removable tempered glass shelves
- Standard commercial stainless steel handle is interchangeable with professional handle accessory
- Door swing is field reversible, and is shipped right hand hinged

# INTEGRATION

- Unit is designed to be built-in or can be freestanding
- Integrated model requires 3/4" custom door panel (panels not supplied by U-Line)
- Four independently adjustable leveling legs provide a precise undercounter fit
- Available in the following finishes: Stainless, Integrated & Black

# **MODEL DETAILS**

Model	Voltage/Hz	Door Swing	Finish	Shipping Weight
U-1215RS-00B	115 / 60	Field Reversible	Stainless Solid	83 lb
U-1215RINT-00B	115 / 60	Field Reversible	Integrated Solid	80 lb
U-1215RB-00B	115 / 60	Field Reversible	Black Solid	83 lb

## **ACCESSORIES**


Model	Description	Finish	Shipping Weight
80-54247-00	Professional Door Handle, 1 1/4" Diameter	Stainless	2 lb




# 1000 Series • 15" Solid Door Refrigerator • 1215R

## **DIMENSIONS**

Dimensions shown apply to all finishes, including Integrated (INT) models with  $34^{\prime\prime}$  integrated panel/frame installed.



#### **CABINET CUT-OUT**



# **SPECIFICATIONS**

Model	1215R	
Amps: Running	1.2	
Capacity: Bottle (12 oz)	57	
Capacity: Can (12 oz)	92	
Capacity: Volume (cu ft)	2.9	
Control Type	Digital Touch Pad	
Dimensions: Product Depth	23 <sup>1</sup> / <sub>4</sub> " / 591 mm	
Dimensions: Product Height	34 ½" / 867 mm	
Dimensions: Product Width	14 <sup>15</sup> / <sub>16</sub> " / 379 mm	
Energy Consumption: Avg. Per Year	225 kWh	
ENERGY STAR / CEE RATING	ENERGY STAR / Tier 3	
Panel Height	30 ½" / 768 mm	
Panel Thickness	<sup>3</sup> / <sub>4</sub> " / 20 mm	
Panel Type	Solid Panel	
Panel Width	14 <sup>3</sup> / <sub>4</sub> " / 375 mm	
Product Weight: Max	76 lb	
Refrigerant Type	R600a	
Sabbath (Star K Certified)	Yes	
Temperature Range	34°F - 45°F	

# **INSTALLATION NOTES**

When installing adjacent to wall, ensure 2  $\frac{1}{2}$ " clearance on hinged side for 90° door opening, allowing ample room for door handle.

Cutout includes the additional  $\frac{1}{4}$ " width overall to ensure proper installation.

No additional clearance around sides, top or rear of unit is needed for ventilation.

Do not obstruct front grille air flow.

## **COOLING SYSTEM**



# **ELECTRICAL REQUIREMENTS**

This unit requires a grounded, polarized 115 VAC, 60 Hz, 15 A power supply (normal household current).









Warranty

Please visit u-line.com to view this model's User Guide & Service Manual. All Specifications are subject to change without notice.