

T24UC905DP

UNDER-COUNTER DOUBLE DRAWER REFRIGERATOR / FREEZER

CUSTOM PANEL-READY



Also Available:
 T24UC925DS - With Professional Series Handle
 T24UC915DS – With Masterpiece® Series Handle

FEATURES & BENEFITS

- Customizable cooling modes in refrigerator drawer — Refrigerator, Pantry, Bar and Quick Chill
- SoftClose® drawers for ultra-smooth closing
- Customizable drawer dividers and shelving
- Filtered Automatic Ice Maker
- LED Lighting
- Drawer mats keep items from sliding and remove for easy cleaning
- Touch electronic controls for temperature management

GENERAL PROPERTIES

| | |
|---|--------------|
| Custom Panel-Ready | Yes |
| SoftClose® Drawers | Yes |
| Lighting | LED Lighting |
| Customizable Aluminum Dividers / Shelving | Yes |
| Removable Drawer Mats | Yes |
| Filtered Automatic Ice Maker | Yes |
| Full Extension Drawers | Yes |
| Drawer Open Alarm | Yes |
| Quick Chill | Yes |
| Touch Electronic Controls | Yes |
| STAR-K Certified Sabbath Mode | Yes |

CAPACITY

| | |
|--------------------------|-------------|
| Total Capacity (cu. ft.) | 4.3 cu. ft. |
|--------------------------|-------------|

TEMPERATURE RANGES

| | |
|-----------------------|---|
| Refrigerator | 33°F (0.5°C) to 47°F (8.5°C) |
| Freezer | -8°F (-22°C) to 6°F (-14.5°C) |
| Pre-Set Cooling Modes | Refrigerator 37°F (3°C) Pantry 44°F (7°C) Bar 34°F (1°C) |
| Quick Chill | Refrigerator 33°F (0.5°C) for approximately 24 hours Freezer -8°F (-22°C) for approximately 24 hours |

TECHNICAL DETAILS

| | |
|-------------------------------------|------------------------|
| Watts (W) / Current (A) / Volts (V) | 150 W / 15 Amp / 115 V |
| Frequency (Hz) | 60 Hz |
| Power Cord Length (in.) | 60" |
| Plug Type | 120V 3-Wire |

DIMENSIONS & WEIGHT

| | |
|--|-----------------------------|
| Appliance Dimensions (H x W x D) (in.) | 34 1/8" x 23 7/8" x 23 5/8" |
| Required Cutout Size (H x W x D) (in.) | 34 1/2"–35 1/8" x 24" x 24" |
| Net / Gross Weight (lbs.) | 144.5 / 155.5 lbs. |

EFFICIENCY

| | |
|---------------------------|---------|
| ENERGY STAR® Qualified | Yes |
| Annual Energy Consumption | 442 kWh |

WARRANTY

Limited, Entire Appliance, Parts and Labor on any Part of the Refrigerator that Fails Because of a Manufacturing Defect

2 Year

Limited Warranty for Sealed Refrigeration System*; Parts and Labor

3rd to 6th Year

Limited Warranty for Sealed Refrigeration System*; Parts Only

7th to 12th Year

*Height adjustable + 1/2" (13 mm) with legs fully extended

**Sealed refrigeration system includes compressor, evaporator, condenser, dryer / strainer and connection tubing


T24UC905DP

UNDER-COUNTER DOUBLE DRAWER REFRIGERATOR / FREEZER


CUSTOM PANEL-READY



DOUBLE DRAWER REFRIGERATOR / FREEZER PRODUCT DIMENSIONS




DOUBLE DRAWER REFRIGERATOR / FREEZER CUTOUT DIMENSIONS



Thermador Double Drawer under counter top dimension. (Unit door flush with cutout)

DOUBLE DRAWER REFRIGERATOR / FREEZER CLEARANCE DIMENSIONS




T24UC905DP

UNDER-COUNTER DOUBLE DRAWER REFRIGERATOR / FREEZER


CUSTOM PANEL-READY



DOUBLE DRAWER REFRIGERATOR / FREEZER SIDE-BY-SIDE INSTALLATION



DOUBLE DRAWER REFRIGERATOR / FREEZER CUTOUT DIMENSIONS & ELECTRICAL LOCATION



ACCESSORIES (OPTIONAL)

HANDLES

NOTE: Choose one handle for each glass door model, choose 2 handles for each double drawer model.



PR20HNDL25
Professional Series Handle (21 1/16" wide)



MS20HNDL25
Masterpiece® Series Handle (20 3/4" wide)

FILTERS



UCTRFLTR10
Water Filter

T24UC905DP

UNDER-COUNTER DOUBLE DRAWER REFRIGERATOR / FREEZER

CUSTOM PANEL-READY




DOUBLE DRAWER REFRIGERATOR CUSTOM PANEL DIMENSIONS – TOP DRAWER PANEL

IMPORTANT:

- The thickness of both the overlay panels must be 3/4" (19mm).
- Overlay panel must not weigh more than 10lbs (4.54kg) each.
- Overlay panels weighing more than recommended may cause damage to your appliance.
- It is recommended to have the help of a second person to install the panel.
- Use the recommended tools in the installation manual to facilitate the installation of the panel. Failure to use the recommended tools or the help of a second person may result in damage to panel and/or the appliance.
- To install the panel, use only the screws included in the "Installation Kit".

Create the custom overlay panel using the dimensions shown.

Top Drawer Panel



T24UC905DP

UNDER-COUNTER DOUBLE DRAWER REFRIGERATOR / FREEZER

CUSTOM PANEL-READY




DOUBLE DRAWER REFRIGERATOR CUSTOM PANEL DIMENSIONS – BOTTOM DRAWER PANEL

IMPORTANT:

- The thickness of both the overlay panels must be 3/4" (19mm).
- Overlay panel must not weigh more than 10lbs (4.54kg) each.
- Overlay panels weighing more than recommended may cause damage to your appliance.
- It is recommended to have the help of a second person to install the panel.
- Use the recommended tools in the installation manual to facilitate the installation of the panel. Failure to use the recommended tools or the help of a second person may result in damage to panel and/or the appliance.
- To install the panel, use only the screws included in the "Installation Kit".

Create the custom overlay panel using the dimensions shown.

Bottom Drawer Panel



These warranties give you specific legal rights and you may have other rights that vary from state to state. Limited warranty from date of purchase. For complete warranty details, refer to your Use & Care manual, or ask your dealer.

Specifications are for planning purposes only. Refer to installation instructions and consult your countertop supplier prior to making counter opening. Consult with a heating and ventilation engineer for your specific ventilation requirements. For the most detailed information, refer to installation instructions accompanying product or write to Thermador indicating the model number. Specifications are correct at time of printing. Thermador reserves the right to change product specifications or design without notice. Some models are certified for use in Canada. Thermador is not responsible for products that are transported from the U.S. for use in Canada.