

100 IC8-T UL

Product Data Sheet



Key points

- Product designed and developed in France by Focal
- 8 Ω or 100V/70V mode by switch
- Low directivity: wide sound dispersion
- Ready-to-paint grille
- UL 1480, UL 2043
- Optional suspended ceiling mounting kit available

Technical Specifications

Type	In-wall/In-ceiling - 2-way coaxial bass-reflex 100V/70V or 8 Ω installations - Steel back can
Drivers	8" (21cm) Polyglass Midbass 1" (25mm) Aluminium inverted dome Tweeter
Sensitivity (2.83V/1m)	91dB
Frequency response (+/-3dB)	53Hz-23kHz
Low frequency point (-6dB)	48Hz
70V line power	7.5/15/30W
100V line power	15/30/60W
8 Ω Recommended amplifier power	15-150W
External dimensions (ØxDepth)	11 ³ / ₄ "x8 ⁷ / ₈ " (297x225mm)
Cut-out diameter	10 ³ / ₈ " (265mm)
Depth from wall	8 ³ / ₈ " (212mm)
Ceiling thickness	0-1 ³ / ₈ " (0-36mm)
Net weight (with grille)	9.37lbs (4.25kg)
Packing dimensions (øxH)	14 ⁵ / ₈ "x11 ³ / ₈ " (370x290mm)
Total weight (with packaging)	11.68lbs (5.3kg)

Selectable power table

8 Ω			
70V	7.5W	15W	30W
100V	15W	30W	60W

