

SUMMARY

DIMENSIONS



CAPACITY
31 cu. ft.

InstaView®
Yes

MEASUREMENTS (WxHxD)
35 3/4" x 70 1/4" x 34 1/4"

ThinQ®
Yes

All Spec

CAPACITY

Refrigerator (cu.ft.)
16.9

Freezer (cu.ft.)
8.6

Total Capacity (cu.ft.)
31

Refrigerator (cu.ft.)
20.4 cu. ft.

Freezer (cu.ft.)
10.3 cu. ft.

Total Capacity (cu.ft.)
30.7 cu. ft.

ENERGY

Energy Consumption (kWh/year)
699

ENERGY STAR® Qualified
Yes

ICE SYSTEM

Dispenser Type

System Type

Integrated Tall Ice & Water Dispenser

Daily Ice Production

3.0 lbs / 3.3 (Ice Plus) 0.7 lbs (Clear big ice) 1.5 lbs (Cubed mini ice)

Ice Storage Capacity

3.0 + 3.8 + 4.0 lbs

IcePlus™

Yes

Water Filter

LT1000P

Slim SpacePlus®

Craft Ice™ Daily Ice Production

6/3

Cube & Crushed Ice

Yes

Dual Ice with Craft Ice™

Yes

UVNano™

Yes

COOLING

Multi Air Flow Cooling:

Yes

Compressor Type

Smart Inverter

Refrigerant [Name / Amount(oz)]

Low GWP, Zero ODP and More Energy Efficient Refrigerant (R600a / 2.01oz)

Temperature Sensors

3

Refrigerant [Name / Amount(g)]

Low GWP, Zero ODP and More Energy Efficient Refrigerant (R600a / 57g)

Fresh Air Filter

Yes

DISPLAY & ETC.

Display Type

Smooth Touch Control / White LED

Door Alarm

Yes (Default)

Decibel™ Quiet Operation

Yes

Auto Closing Door Hinge

Yes

ThinQ®

Yes

Sabbath

Yes

Temperature Controls

Electronic/Digital

Child Lock

Yes

Smart Diagnosis

Yes

wi-fi Enabled

Yes

Special Features

Door Cooling+

REFRIGERATOR

Door-in-Door®

Yes

Folding Shelf

1

Shelf Construction

SpillProof™ Tempered Glass

Glide N' Serve™ Drawer

Yes

Handle Type

Bar

Door Bin Construction

1 Piece (Clear)

No. of Shelves

4 Split(3 Fixed+1Folding)

Cantilevered Shelves

Hybrid Cantilevered

Crisper Bins

2 Crispers

CoolGuard™

Yes

No. of Door Bins

8 Total (2 Adjustable Gallon Sized)

FREEZER

Door Type	Drawers/Shelves
Pull Drawer	3-Tier Organization
DuraBase™ Solid Drawer Base	Freezer Light Upper
Yes	LED Lighting
Freezer Handle	
SmartPull™ Handle	

MATERIALS & FINISHES

Flat type Door	Hidden Hinges
Yes	Yes
Surface	Handles
Smooth	Matching Commercial Handles
Smudge Resistant Finish	Insulation
Yes	Low GWP and Zero ODP Blowing Agent

DIMENSIONS

Width	Height to Top of Hinge
35 3/4"	70 1/4"
Depth with Handles	Depth (with handles)
31 5/8"	34 1/4"
Width (Door Open 90° without Handle)	Width (Door Open 90° with Handle)
40"	44 7/8"
Door Edge Clearance with Handle	Door Edge Clearance without Handle
4 1/4"	2 1/4"
Height to Top of Case	Depth without Door
68 7/8"	24 7/8"
Depth without Door	Depth without Handles
29 7/8"	29 1/4"
Depth without Handles	Depth (Total with Door Open)
34 1/4"	43 1/2"
Depth (Total with Door Open)	Depth (Draw Open Fully without Handle)
48 3/4"	48 7/8"
Installation Clearance	Weight (Unit/Carton)
Sides 1/8", Top 1", Back 2"	322 lbs / 352 lbs
Weight (Unit/Carton)	Carton Dimensions (WxHxD)
317 lbs. / 339 lbs.	38" x 73" x 32"
Carton dimensions (W x H x D)	
38" x 72" x 37"	

LIMITED WARRANTY

Parts & Labour	Sealed System (Parts only)
1 Year	7 Years
Compressor (Parts Only)	
10 Years	

UPC

UPC
195174034811