

GENERAL			
Number of Channels	4	Amplifier Class	Class FD
Maximum Power Output	400W	Maximum Power Output at 2 ff	100W x 4
Maximum Power Output at 4 ff	100W x 4	Maximum Power Output - Bridged at 4 ff	200W x 2
Nominal Power (RMS) Output at 2 ff	45W x 4	Nominal Power (RMS) Output at 4 ff	45W x 4
Nominal Power (RMS) Output - Bridged at 4 ff	90W x 2	Frequency Response	10 Hz to 40 kHz
Total Harmonic Distortion (THD)	< 0.05% (1 kHz)	Signal-to-Noise (SN) Ratio	75 dB
Fuse Rating	15 Amps		

SPECIFICATIONS			
RCA Inputs	4-Ch.	Speaker Level Inputs	✔
Crossover Type	LPF/HPF	Low-Pass Crossover Frequency	80 Hz (LPF/OFF/HPF)
Low Pass Slope (dB/octave)	-12 dB/octave	High-Pass Crossover Frequency	80 Hz (LPF/OFF/HPF)
High-Pass Slope (dB/octave)	-12 dB/octave	Automatic Signal Sensing and Turn-On	✔
Terminal Type	Removable	Load Impedance Allowance (Ω)	1 to 8
Bridgeable	✔	MOSFET Output Selection	✔
Protection Control System	✔	Dimensions (WxHxD)(inches)	7-1/8" x 1-1/2" x 2-1/2"
Warranty	1 Year		