

IPEG-D20F-IRW4

2MP Vandal Proof Dome Network Camera



- 2MP, 1/2.8" CMOS image sensor, low illuminance, high image definition
- H.265 & H.264 dual-stream encoding
- 2MP (1920 × 1080)@25/30 fps
- DWDR, 3D DNR, HLC, BLC
- 2.8 mm fixed lens
- Starlight support, Max. IR LEDs Length 98ft
- IP67, IK10, PoE

System Overview

The IPEG-D20F-IRW4 is a Vandal-Proof Dome style camera in IC Realtime's cost-effective Edge lineup. This camera comes packed with high end features including H.265 encoding with DWDR for a more colorful image in daylight as well as low illumination environments and IR distance up to 98ft.

The H.265 encoding technology provides a more efficient video encoding capacity, and saves bandwidth and storage space compared to H.264. In addition, it is waterproof, dust-proof and tamper-proof by complying to IP67 and IK10 standards.

Functions

Environmental

With a temperature range of -40°F to +140°F (-40°C to +60°C), the camera is designed for extreme temperature environments. The camera complies to an IK10 impact rating making it capable of withstanding the equivalent of 120 lbs (55 kg) of force. Subjected and certified to rigorous dust and water immersion tests, the IP67 rating makes it suitable for demanding outdoor applications. For environments with rain, sleet, snow and fog, an integrated wiper provides users with clear visibility at all times.

Protection

The camera's outstanding reliability is unsurpassed due to its rugged design. The camera is protected against water and dust with IP67 rating, making it suitable for indoor or outdoor environments.

The camera complies with an IK10 vandal resistance rating making it capable of withstanding the equivalent of 5 kg (11.02 lbs) of force dropped from a height of 40 cm (15.75 in).

Smart H.265+

Deliver high quality video without straining the network, Smart H.265+ is the optimized implementation of H.265. The Smart H.265+ encoding technology includes a scene adaptive encoding strategy, dynamic GOP, dynamic ROI, flexible multi-frame reference structure and intelligent noise reduction, providing saving of up to 70% of bandwidth and storage when compared with standard H.265.

Interoperability

The camera conforms to the ONVIF (Open Network Video Interface Forum) specifications, ensuring interoperability between network video products regardless of manufacturer.

Smart IR Technology

With IR illumination, detailed images can be captured in low light or total darkness. The camera's Smart IR technology adjusts the intensity of camera's infrared LEDs to compensate the distance of an object. Smart IR technology prevents IR LEDs from whitening out images as they come closer to the camera. The camera's integrated infrared illumination provides high performance in extreme low-light environments up to 98ft (30m).

Technical Specification

Camera

Image Sensor	1/2.8" 2 Megapixel progressive CMOS
Effective Pixels	1920(H) x 1080(V), 2 Megapixels
RAM/ROM	64MB /16MB
Scanning System	Progressive
Electronic Shutter Speed	Auto/Manual 1/3 s-1/100000 s
Minimum Illumination	0.01 Lux @F2.0
S/N Ratio	More than 56dB
IR Distance	98.43 ft (Distance up to 30 m)
IR On/Off Control	Auto / Manual
IR LEDs	3

Lens

Lens Type	Fixed				
Mount Type	M12				
Focal Length	2.8mm				
Max. Aperture	F2.0				
Angle of View	Horizontal: 102°; Vertical: 54°				
Optical Zoom	N/A				
Focus Control	Fixed				
Close Focus Distance	1.6 ft (0.5 m)				
DORI Distance	Lens	Detect	Observe	Recognize	Identify
	2.8 mm	123ft	50ft	25ft	12ft

Pan/Tilt/Rotation

Pan/Tilt/Rotation Range	Pan: 0°-355°Tilt: 0°-65°Rotation: 0°-355°
-------------------------	---

Video

Compression	H.265; H.264; H.264B; MJPEG (Sub stream only)
Streaming Capability	2 Streams
Resolution	1080p (1920 × 1080); 1.3M (1280 × 960); 720p (1280 × 720); D1 (704 × 576/704 × 480); VGA (640 × 480); CIF(352 × 288/352 × 240)
Frame Rate	Main Stream: 1920 × 1080 (1 fps-25/30 fps)
	Sub Stream: 704 × 576 (1 fps-25fps) 704 × 480 (1 fps-30fps)
Bit Rate Control	CBR/VBR
Bit Rate	H.264: 32 kbps-6144 kbps H.265: 12 kbps-6400 kbps
Day/Night	Auto(ICR) / Color / B/W
BLC Mode	BLC / HLC / DWDR
White Balance	Auto/natural/street lamp/outdoor/manual/regional custom
Gain Control	Auto / Manual
Noise Reduction	3D DNR
Motion Detection	Off / On (4 Zone, Rectangle)
Region of Interest	Off / On (4 Zone)

Smart IR	Support
Starlight	Support
Digital Zoom	16x
Flip	0°/90°/180°/270° (Supports 90°/270° with 1080p resolution.)
Mirror	Off / On
Privacy Masking	Off / On (4 Area, Rectangle)

Audio

Compression	N/A
-------------	-----

Network

Ethernet	RJ-45 (10/100Base-T)
Protocol	IPv4; IPv6; HTTP; TCP; UDP; ARP; RTP; RTSP; SMTP; FTP; DHCP; DNS; NTP; Multicast
Interoperability	ONVIF (Profile S/Profile T); CGI; P2P
Cyber Security	Video encryption; configuration encryption; Digest; WSSE; account lockout; security logs; generation and importing of X.509 certification; HTTPS; trusted boot; trusted execution; trusted upgrade
Streaming Method	Unicast / Multicast
Max. User Access	6 (Total bandwidth: 36 M)
Edge Storage	FTP
Web Viewer	IE, Chrome, Firefox, Safari
Management Software	SmartICRSS, DSS
Smart Phone	IOS, Android

Certifications

Certifications	FCC Part 15, Subpart B
----------------	------------------------

Interface

Video Interface	N/A
Audio Interface	N/A
RS485	N/A
Alarm	N/A

Electrical

Power Supply	DC12V, PoE (802.3af)
Power Consumption	Basic power consumption: 1.6W (12V DC); 2.2W (PoE) Max. power consumption (ICR + H.265 + IR intensity): 4.4W (12V DC); 5.1W (PoE)

Environmental

Operating Conditions	-40°F to +140°F (-40°C to +60°C)/less than ≤ 95% RH
Storage Conditions	-40°F to +140°F (-40°C to +60°C)
Ingress Protection	IP67
Vandal Resistance	IK10



Construction

Casing	Metal
Dimensions	3.2" × Φ4.3" (81 mm × Φ109.9 mm)
Net Weight	0.7 lb (0.35 kg)
Gross Weight	1.1 lb (0.50 kg)

Accessories

Dimensions (mm/in)

MNT-JUNCTION-BOX-6



MNT-IPMINIDOME-WALL

