



LYNX PROFESSIONAL GRILL SERIES

54" PROFESSIONAL FREESTANDING GRILL

TRIDENT™ AND CERAMIC WITH ROTISSERIE (L54TRF)



L54TRF PRODUCT OVERVIEW

- Precise power—one Trident™ Infrared Burner and three Cast Ceramic Burners combining to provide up to 98,000 BTU
- Reliable speed—Hot Surface Ignition system lights burners quickly and safely
- Perfect clarity—dual halogen grill surface lights
- Quick visibility—temperature gauge
- Easy opening—Lynx Hood Assist
- Slow-cooking excellence—with a dual-position rotisserie with 2 14,000 btu burners, internally powered by a heavy-duty three-speed motor, delivering up to 28,000 BTU
- Indulgent extra—premium smoker box included
- Generous capacity—1,555 square inches of cooking surface (1,110 primary, 445 secondary)
- Beautiful illumination—blue-lit control knobs
- Steady performance—heat-stabilizing design
- Smooth opening—fluid rotation handle
- Premier platform—stainless steel grilling grates
- Steadfast durability—heavy-duty welded construction eliminates gaps where grease can collect



FOR A COMPLIMENTARY CUSTOM DESIGN FOR YOUR OUTDOOR KITCHEN, VISIT LYNXGRILLS.COM/DESIGN-CENTER

L54TRF PRODUCT FEATURES

Our unrelenting attention to detail and our passion for innovation have fostered the stunning features that define the Lynx Professional Series. These features begin with meticulous hand-crafted excellence, and they culminate in powerful capabilities that give you precision control.



TRIDENT™ INFRARED BURNER



CERAMIC RADIANT BRIQUETTES



SEAMLESS WELDED CONSTRUCTION



HEAT STABILIZING DESIGN



HOT SURFACE IGNITION



EXPANSIVE GRILLING SURFACE



ROTISSERIE SYSTEM



SMOKER BOX



INTEGRATED ILLUMINATION



CERAMIC BURNER



LYNX HOOD ASSIST

FOR MORE
INFORMATION ON
LYNX PROFESSIONAL
PRODUCT FEATURES,
PLEASE VISIT
LYNXGRILLS.COM

PRODUCT TECHNICAL SPECIFICATIONS



PRODUCT DIMENSIONS: WIDTH: 67 ¾" / HEIGHT: 50" / DEPTH: 27 ¾"



SHIPPING DIMENSIONS: WIDTH 63 ½" / HEIGHT 54" / DEPTH 34"
SHIPPING WEIGHT: 627 POUNDS



GAS REQUIREMENTS: SHIPS IN LIQUID PROPANE OR NATURAL GAS FROM FACTORY



ELECTRICAL REQUIREMENTS: INSTALLATION REQUIRES AN OUTDOOR 120V/15GFI ELECTRICAL OUTLET ADJACENT TO PRODUCT



COOKING CONFIGURATION: FREESTANDING GRILL WITH 1 TRIDENT™ INFRARED BURNER AND 3 CERAMIC BURNERS AND ROTISSERIE