

SPECIAL ORDER

COMMERCIAL THROUGH RETAIL PREP FOR CARD TOP LOAD WASHER & MATCHING DRYER

Built for Reliable Performance

Huebsch® prep for card top load washer and matching dryer combine heavy-duty construction with reliable operation proven to stand the test of time. With features such as water and energy efficient designs, quality internal components and high security systems, owners can depend on Huebsch.



Top Load Washer
Control Panel



Dryer Control Panel

Washer:

- Touch pad control with sound annunciator
- 27 cycle selections
- Multi-level vend pricing
- Extract speed of 710 RPM spins clothes out drier

Dryer:

- Integrated meter case
- Upfront lint filter easy to clean and secured
- Perfect balance of heat, airflow and tumble action for optimal performance and efficiency
- High efficiency exhaust blower with superior airflow 220 cfm (105 liters/sec)



COMMERCIAL THROUGH RETAIL - SPECIAL ORDER

PREP FOR CARD

TOP LOAD WASHER & MATCHING DRYER



Product		Top Load Washer
Color		White
Capacity - lb (kg)		16 (7.3)
Cylinder Volume - cu.ft. (liters)		3.19 (90.3)
Spin Speed G-Force (RPM)		150 (710)
Motor Size - HP (kw)		0.5 (0.37)
Water Consumption Per Cycle - g (liter)*		28.07 (106)
IWF (Water Factor) - gal/ft³ (liters/liter/cycle)*		8.8 (1.18)
MEF ₃₂ (Modified Energy Factor) ft³/kWh/cycle (Liters/kWh/cycle)*		1.35 (38.2)
Available Water Temperatures		Cold, Warm, Hot
Available Cycles		Normal, Synthetic, Delicate
Electrical Requirements (v/Hz/Ph-Amp)		120/60/1 - 15 Amp
Water Pressure - p.s.i (bar)		20-120 (1.4/8.3)
Drain		Pump
Cylinder Finish		Stainless Steel
Net Weight - lb (kg)		206 (93.4)
Shipping Weight - lb (kg)		218 (98.8)
Shipping Dimensions Approx. - in	Width	28
	Depth	30
	Height	45
Agency Approvals		cULus
Model No.		HWNKY2SP116CW01

Product		Dryer
Color		White
Capacity - lb (kg)		18 (8.2)
Cylinder Volume - cu.ft. (liters)		7.0 (198)
Motor (Thermal Protected)		0.33 HP
Air Outlet Diameter - in		4
Exhaust Airflow - cfm (liters/sec)		220 (105)
Available Cycles		High, Medium, Low, Delicates, No Heat
Electrical Requirements	**Electric	208-240/60/1-30 Amp
Heating Element	Electric	5000W, 240V / 4250W, 208V
Net Weight - lb (kg)		150 (68)
Shipping Weight - lb (kg)		161 (73)
Shipping Dimensions Approx. - in	Width	30.5
	Depth	29.5
	Height	45
Agency Approvals		cULus
Model No.		HDENYRGS176CW01

Dimensions	Width - in	Height - in	Depth - in	Floor to Door Opening - in	Door Swing - in
Top Load Washer	25.625	43	28	51	—
Dryer	26.875	43	28	15.44	23.5

For Commercial Use Only

* Average usage based on multiple load sizes and current DOE test protocol. Real usage will vary depending on load size, composition and cycle selectivity.

** Electric dryers are dual rated for 208-240V applications. Using dryer in 208V will reduce the wattage output. An optional kit (965P3) can be used to field convert the unit for 4250 output at 208V.

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications are subject to change without notice. The quality management systems of Alliance Laundry Systems are registered to ISO 9001.