

## Refrigeration Equipment Undercounter Refrigerator, 72" with 3 Doors with Worktop - Stainless Steel (R600a)

ITEM # \_\_\_\_\_  
MODEL # \_\_\_\_\_  
NAME # \_\_\_\_\_  
SIS # \_\_\_\_\_  
AIA # \_\_\_\_\_



738302 (KCHUCWT72R)

3-door undercounter refrigerator with worktop, 72", R600a refrigerant gas, 33/+41°F, stainless steel

### Short Form Specification

#### Item No.

3-door refrigerated counter top with exterior back panel in aluminium, exterior bottom panel in galvanized steel, exterior side and top panel in 430 stainless steel; interior back, top and bottom panels in 304 stainless steel.

Fin & tube condenser to improve the performances in high temperature environments. Automatic Defrost Cooling System and temperature control. Vinyl heavy duty adjustable, easy to handle and clean shelves. External temperature display.

R600a gas in refrigeration circuit.  
ETL Safety and Sanitation certified.  
3/5 Years warranty.

### Main Features

- External temperature display.
- Removable gasket for easy cleaning operations.
- Fin & Tube Condenser improves performance in high temperature environments.
- Automatic Defrost Cooling System provides worry-free performance.
- Electronic Temperature Control, quick and simple to set, with control display for easy monitoring.
- Heavy duty Vinyl coated steel shelves.
- High efficiency components to minimize the energy consumption still guaranteeing the highest performances.
- Cabinet completely insulated with high density polyurethane for low environmental impact.


### Construction

- Self-closing door with 90-degree stay-open feature.
- Heavy duty casters.
- CFC and HCFC free (ecological refrigerant type: R600a).
- Pre-wired heavy duty power cord.
- Heavy duty door hinges.
- Magnetic gasket removable without tools for easy cleaning.

### Optional Accessories

- shelf for 48" and 72" (left/right) mega top, salad and undercounter PNC 880597 ☐
- middle shelf for 72" mega top, salad and undercounter PNC 880598 ☐
- shelf clips PNC 880611 ☐

APPROVAL: \_\_\_\_\_



EI = Electrical connection

## Electric

### Supply voltage:

738302 (KCHUCWT72R) 115 V/1 ph/60 Hz

### Electrical power, max:

0.4 kW

### Current consumption:

3.5 Amps

### Plug type:

USA NEMA 5-15P

## Key Information:

### Door hinges:

Right Side

### External dimensions, Width:

71 3/4" (1822 mm)

### External dimensions, Depth:

29 15/16" (760 mm)

### External dimensions, Height:

39 7/16" (1002 mm)

### Number and type of doors:

3 Full

### Internal Dimensions (depth):

22 13/16"

### Internal Dimensions (height):

23 1/2"

### Internal Dimensions (width):

22 1/4"

### Shipping height:

42 1/8" (1070 mm)

### Shipping weight:

379 lbs (172 kg)

### Shipping volume:

56.28 ft<sup>3</sup> (1.59 m<sup>3</sup>)

### Number and type of grids (included):

3 - Vinyl-Coated Steel

### Type of external material:

Stainless Steel

### Type of internal material:

Polystyrene

### Warranty:

3 / 5 years

## Refrigeration Data

### Compressor Horsepower:

1/6

### Refrigerant type:

R600a

### Refrigerant weight:

125 g

### Operating temperature min.:

32 °F

### Operating temperature max.:

41 °F

### Condenser type:

Fin & tube

### Defrost type:

Auto Defrost

## Product Information (EU Regulation 2015/1094)

### Capacity (Cu. Ft.)

72