

1215RSOD • 15" Outdoor Refrigerator • Outdoor Series





STAINLES SOLID (LOCK)

FEATURES & BENEFITS

PERFORMANCE

- Overall volume of 2.9 cu ft holds up to 57 bottles (12 oz) or 92 cans (12 oz)
- Digital Touch Pad Control is conveniently located on upper face of unit
- Temperature range: 34°F 45°F
- Digital passive cooling system

INTERIOR/EXTERIOR

- White interior is illuminated with LED lighting
- Three removable tempered glass shelves
- Standard professional stainless steel handle is interchangeable with commercial handle accessory
- Full stainless steel cabinet and door are deemed suitable for outdoor use by UL
- Door swing is field reversible
- Door lock is standard

INTEGRATION

- Unit is designed to be built-in or can be freestanding
- Four independently adjustable leveling legs provide a precise undercounter fit

MODEL DETAILS

Model	Voltage	Door Swing	Finish	Shipping Weight
U-1215RSOD-00A	115	Field Reversible	Stainless Solid (Lock)	83 lbs

ACCESSORIES


Model	Description	Finish	Shipping Weight
23074	Professional Door Handle, 1 ¼" Diameter	Stainless	2 lbs
23073	Commercial Door Handle, 7/8" Diameter	Stainless	2 lbs




Outdoor Series • 15" Outdoor Refrigerator • 1215RSOD

DIMENSIONS

Dimensions shown apply to all finishes.



CABINET CUT-OUT



SPECIFICATIONS

Model	1215RSOD	
Amps: Running	1.2	
Capacity: Bottle (12 oz)	57	
Capacity: Can (12 oz)	92	
Capacity: Volume (cu ft)	2.9	
Capacity: Wine Bottle (750 ml)	na	
Control Type	Digital Touch Pad	
Dimensions: Depth	23 ¹ / ₄ " / 591 mm	
Dimensions: Height	34 ½" / 867 mm	
Dimensions: Width	14 ¹⁵ / ₁₆ " / 379 mm	
Energy Consumption: Avg. Per Year	225 kWh	
ENERGY STAR	ENERGY STAR	
Product Weight: Max	76 lbs	
Refrigerant Type	R600a	
Sabbath (Star K Certified)	Yes	
Temperature Range	34°F - 45°F	

INSTALLATION NOTES

When installing adjacent to wall, ensure 2-1/2'' clearance on hinged side for 90° door opening, allowing ample room for door handle.

Cutout includes the additional $1/4^{\prime\prime}$ width overall to ensure proper installation.

No additional clearance around sides, top or rear of unit is needed for ventilation.

Do not obstruct front grille air flow.

COOLING SYSTEM



ELECTRICAL REQUIREMENTS

This unit requires a grounded a polarized 115 VAC, $60~{\rm Hz}$, $15~{\rm A}$ power supply (normal household current).







Please visit u-line.com to view this model's User Guide. All specifications are subject to change without notice.

Residential & Commercial Deemed suitable for outdoor use by UL