Specifications

■ Front, surround speakers (NS-B40) and center speaker (NS-C40)

Type
NS-B40 ..... Full range bass reflex non magnetic shielding type
NS-C40 ..... Full range acoustic suspension non magnetic shielding type
Driver ..... 7 cm (2-3/4") cone type
Nominal input power ..... 30 W
Maximum input power ..... 100 W
Impedance ..... 6 Ω
Frequency response
NS-B40 ..... 50 Hz–25 kHz (–10 dB) –45 kHz (–30 dB)
NS-C40 ..... 70 Hz–25 kHz (–10 dB) –45 kHz (–30 dB)
Sensitivity
NS-B40 ..... 83 dB/2.83 V, 1 m
NS-C40 ..... 84 dB/2.83 V, 1 m
Dimensions (W x H x D)
NS-B40 ..... 112 x 176 x 116 mm (4-3/8" x 6-7/8" x 4-5/8")
NS-C40 ..... 276 x 111 x 118 mm (10-7/8" x 4-3/8" x 4-5/8")
Weight
NS-B40 ..... 0.59 kg (1.30 lbs.)
NS-C40 ..... 0.73 kg (1.61 lbs.)

■ Subwoofer (NS-SW050)

Type ..... Advanced Yamaha Active Servo Technology II
Driver ..... 20 cm (8") cone woofer non magnetic shielding type
Amplifier Output (100 Hz, 5 Ω, 10% T.H.D) ..... 50 W
Dynamic Power ..... 100 W, 5 Ω
Frequency response ..... 28 Hz–200 Hz
Power supply
USA and Canada models ..... AC 120 V, 60 Hz
Asia and General models ..... AC 110-120/220-240 V, 50/60 Hz
Power Consumption ..... 40 W
Dimensions (W x H x D) ..... 291 x 292 x 341 mm (11-1/2" x 11-1/2" x 13-3/8")
Weight ..... 8.5 kg (18.7 lbs.)

* The contents of this manual apply to the latest specifications as of the publishing date. To obtain the latest manual, access the Yamaha website then download the manual file.