

ELECTRICAL	Impedance(Ω)	4 Ω	
	Peak Input Power (W)	300W	
	RMS Input Power (W) CTA standards	100W	
	Sensitivity (dB at 1m) CTA standards	84dB	
	Frequency Response(Hz) CTA standards	45-23,000Hz	
Woofer	Diaphragm	PP Cone	
	Size	153x229mm	6x9 inch
	Surround	Rubber	
	Basket	Steel	
	Magnet	Ferrite	ϕ 90x15
Midrange	Diaphragm	PP Cone	+Sub Cone
	Size	44mm	2-3/4 inch
	Surround	Cloth	
	Basket	Plastic	
	Magnet	Ferrite	ϕ 50x18
Newtwork	Midrange	HPF	-6dB/oct, 850Hz
	Woofer	LPF	-6dB/oct, 850Hz Bypass Selectable inch
	Woofer		
	Width	236.4 mm	9-5/16
	Height	164 mm	6-7/16
	Top Height	82.3 mm	3-1/4 in.
	Cutout Diameter	217 x 145 mm	8-9/16 x 5-11/16 in.

ELECTRICAL	Impedance(Ω)	4 Ω	
	Peak Input Power (W)	300W	
	RMS Input Power (W) CTA standards	100W	
	Sensitivity (dB at 1m) CTA standards	84dB	
	Frequency Response(Hz) CTA standards	45-23,000Hz	
Woofer	Diaphragm	PP Cone	
	Size	153x229mm	6x9 inch
	Surround	Rubber	
	Basket	Steel	
	Magnet	Ferrite	ϕ 90x15
Midrange	Diaphragm	PP Cone	+Sub Cone
	Size	44mm	2-3/4 inch
	Surround	Cloth	
	Basket	Plastic	
	Magnet	Ferrite	ϕ 50x18
Newtwork	Midrange	HPF	-6dB/oct, 850Hz
	Woofer	LPF	-6dB/oct, 850Hz Bypass Selectable inch
	Woofer		
	Width	236.4 mm	9-5/16
	Height	164 mm	6-7/16
	Top Height	82.3 mm	3-1/4 in.
	Cutout Diameter	217 x 145 mm	8-9/16 x 5-11/16 in.

ELECTRICAL	Impedance(Ω)	4 Ω	
	Peak Input Power (W)	300W	
	RMS Input Power (W) CTA standards	100W	
	Sensitivity (dB at 1m) CTA standards	84dB	
	Frequency Response(Hz) CTA standards	45-23,000Hz	
Woofer	Diaphragm	PP Cone	
	Size	153x229mm	6x9 inch
	Surround	Rubber	
	Basket	Steel	
	Magnet	Ferrite	ϕ 90x15
Midrange	Diaphragm	PP Cone	+Sub Cone
	Size	44mm	2-3/4 inch
	Surround	Cloth	
	Basket	Plastic	
	Magnet	Ferrite	ϕ 50x18
Newtwork	Midrange	HPF	-6dB/oct, 850Hz
	Woofer	LPF	-6dB/oct, 850Hz Bypass Selectable inch
	Woofer		
	Width	236.4 mm	9-5/16
	Height	164 mm	6-7/16
	Top Height	82.3 mm	3-1/4 in.
	Cutout Diameter	217 x 145 mm	8-9/16 x 5-11/16 in.

ELECTRICAL	Impedance(Ω)	4 Ω	
	Peak Input Power (W)	300W	
	RMS Input Power (W) CTA standards	100W	
	Sensitivity (dB at 1m) CTA standards	84dB	
	Frequency Response(Hz) CTA standards	45-23,000Hz	
Woofer	Diaphragm	PP Cone	
	Size	153x229mm	6x9 inch
	Surround	Rubber	
	Basket	Steel	
	Magnet	Ferrite	ϕ 90x15
Midrange	Diaphragm	PP Cone	+Sub Cone
	Size	44mm	2-3/4 inch
	Surround	Cloth	
	Basket	Plastic	
	Magnet	Ferrite	ϕ 50x18
Newtwork	Midrange	HPF	-6dB/oct, 850Hz
	Woofer	LPF	-6dB/oct, 850Hz Bypass Selectable inch
	Woofer		
	Width	236.4 mm	9-5/16
	Height	164 mm	6-7/16
	Top Height	82.3 mm	3-1/4 in.
	Cutout Diameter	217 x 145 mm	8-9/16 x 5-11/16 in.

ELECTRICAL	Impedance(Ω)	4 Ω	
	Peak Input Power (W)	300W	
	RMS Input Power (W) CTA standards	100W	
	Sensitivity (dB at 1m) CTA standards	84dB	
	Frequency Response(Hz) CTA standards	45-23,000Hz	
Woofer	Diaphragm	PP Cone	
	Size	153x229mm	6x9 inch
	Surround	Rubber	
	Basket	Steel	
	Magnet	Ferrite	ϕ 90x15
Midrange	Diaphragm	PP Cone	+Sub Cone
	Size	44mm	2-3/4 inch
	Surround	Cloth	
	Basket	Plastic	
	Magnet	Ferrite	ϕ 50x18
Newtwork	Midrange	HPF	-6dB/oct, 850Hz
	Woofer	LPF	-6dB/oct, 850Hz Bypass Selectable inch
	Woofer		
	Width	236.4 mm	9-5/16
	Height	164 mm	6-7/16
	Top Height	82.3 mm	3-1/4 in.
	Cutout Diameter	217 x 145 mm	8-9/16 x 5-11/16 in.

JA

ELECTRICAL	Impedance(Ω)	4 Ω	
	Peak Input Power (W)	300W	
	RMS Input Power (W) CTA standards	100W	
	Sensitivity (dB at 1m) CTA standards	84dB	
	Frequency Response(Hz) CTA standards	45-23,000Hz	
Woofer	Diaphragm	PP Cone	
	Size	153x229mm	6x9 inch
	Surround	Rubber	
	Basket	Steel	
	Magnet	Ferrite	ϕ 90x15
Midrange	Diaphragm	PP Cone	+Sub Cone
	Size	44mm	2-3/4 inch
	Surround	Cloth	
	Basket	Plastic	
	Magnet	Ferrite	ϕ 50x18
Newtwork	Midrange	HPF	-6dB/oct, 850Hz
	Woofer	LPF	-6dB/oct, 850Hz Bypass Selectable inch
	Woofer		
	Width	236.4 mm	9-5/16
	Height	164 mm	6-7/16
	Top Height	82.3 mm	3-1/4 in.
	Cutout Diameter	217 x 145 mm	8-9/16 x 5-11/16 in.