

BIM470S



33" x 14.5" x 23.5" (H x W x D)

15" wide 50 lb. built-in undercounter commercially listed outdoor clear icemaker with automatic defrost, internal pump, and complete stainless steel exterior

Highlights:

Weatherproof construction for use in the outdoors

Commercially approved to NSF-12 standards

Commercial ENERGY STAR certification

Product Features:

Commercially approved	ETL-S listed to NSF-12 commercial standards
Weatherproof design	Durable stainless steel construction for safe installation in outdoor spaces
Built-in capable	Make the best use of space by installing your icemaker under the counter
50 lb. production capacity	Can make up to 50 lbs. of clear ice cubes in a day cycle and store up to 25 lbs. per day (Note: ice is produced in sheets and can easily be broken into cubes using the provided scoop.)
ENERGY STAR certified commercial performance	Efficient performance saves on energy use and costs
Built-in pump	Internal pump affords more flexibility in placing the unit
Automatic defrost	Reduced maintenance with auto defrost system
Clear ice cube production	Produces 3/4" x 3/4" x 1" clear ice cubes
Touch control panel	Provides easy operation of the unit with indicator lights for each stage of the production process





BIM47OS Specifications:

Height of Cabinet 33.0" (84 cm) Width 14.5" (37 cm) Depth 23.5" (60 cm) Depth with Handle 25.0" (64 cm) Depth with door at 90° 37.0" (94 cm) Defrost Type Automatic Door Stainless Stee Cabinet Stainless Stee
Depth 23.5" (60 cm) Depth with Handle 25.0" (64 cm) Depth with door at 90° 37.0" (94 cm) Defrost Type Automatic Door Stainless Stee Cabinet Stainless Stee
Depth with Handle 25.0" (64 cm) Depth with door at 90° 37.0" (94 cm) Defrost Type Automatic Door Stainless Stee Cabinet Stainless Stee
Depth with door at 90° 37.0" (94 cm) Defrost Type Automatic Door Stainless Stee Cabinet Stainless Stee
Defrost Type Automatic Door Stainless Stee Cabinet Stainless Stee
Door Stainless Stee Cabinet Stainless Stee
Cabinet Stainless Stee
US Electrical Safety UL
Canadian Electrical ULC Safety
Sanitation ETL-S
Amps 4.8
Voltage/Frequency 115 V AC/60 Hz
Weight 100.0 lbs. (45 kg)
Shipping Weight 105.0 lbs. (48 kg)
Parts & Labor Warranty 1 Year
Compressor Warranty 5 Years
Icemaker
Door Swing LHD
Reversible Yes
Drain Required Yes
Daily Ice Production 50.0 lbs. (23 kg)
Ice Storage Capacity 25.0 lbs. (11 kg)
Ice Shape Cube
Size of Cube 3/4" x 3/4" x 1
Number of Ice Cube Sizes 1
Number of Ice Cube Sizes 1 Fan Type Exterior
Fan Type Exterior
Fan Type Exterior Refrigerant Type R134a
Fan Type Exterior Refrigerant Type R134a Refrigerant Amount 3.88 oz
Fan Type Exterior Refrigerant Type R134a Refrigerant Amount 3.88 oz High Side PSI 350.0
Fan Type Exterior Refrigerant Type R134a Refrigerant Amount 3.88 oz High Side PSI 350.0 Low Side PSI 130.0
Fan Type Exterior Refrigerant Type R134a Refrigerant Amount 3.88 oz High Side PSI 350.0 Low Side PSI 130.0 Interior Height 18.5" (47 cm)



