SPECIFICATION SHEET

best

MODEL P195ES52SB POWER PACK



ENERGY STAR® efficiency for custom applications provides the ventilation and lighting you need in one integrated package.

FEATURES

- 3-speed control
- Centrifugal blower, 290 CFM, 5.0 Sones
- 6" round duct connector/backdraft damper
- Enclosed light
- Two 13 Watt, G24Q-1 compact fluorescent lamps (included)
- One piece washable aluminum mesh filter
- 430 stainless steel finish
- Heat Sentry[™] automatically turns blower to high speed when excess cooking heat is detected
- Fully enclosed bottom
- Power supply cord included
- One Year Limited Warranty
- For indoor use only

OPTIONS

- Protect cabinet with Model L5230 Stainless Steel Liner
- Recirculation filter Model FILTEREB40

SPECIFICATIONS

VOLTS	ΗZ	AMPS	CI	=M	SONES		DUCT
			MAX.	NORM.	MAX.	NORM.	
120	60	2.8	290	120	5.0	0.5	6" round



HVI-2100 CERTIFIED RATINGS comply with new testing technologies and procedures prescribed by the Home Ventilating Institute, for off-the-shelf products, as they are available to consumers. Product performance is rated at 0.1 in static pressure, based on tests conducted in a state-of-the-art test laboratory. Sones are a measure of humanly-perceived loudness, based on laboratory measurements.

Power Pack shall be Best Model P195ES52SB. Power Pack shall have a 3-speed fan switch and separate light switch.

TYPICAL SPECIFICATION

Fan must be ducted and use a washable aluminum mesh filter.

Unit shall have a 430 stainless steel finish.

Air delivery to be at least 290 CFM and sound levels not greater than 5.0 Sones.

Unit shall be UL and cUL listed.

Air and sound ratings to be certified by HVI.

Unit shall be ENERGY STAR® certified.







BEST® Hartford, Wisconsin www.BestRangeHoods.com 800-558-1711

REFERENCE	QTY.	REMARKS	Project	
			Location Architect Engineer Contractor	
			Submitted by	Date