

GENERAL			
Number of Channels	2	Amplifier Class	Class AB
Maximum Power Output	500W	Maximum Power Output at 2 ff	250W x 2
Maximum Power Output at 4 ff	170W x 2	Maximum Power Output - Bridged at 4 ff	500W
Nominal Power (RMS) Output at 2 ff	95W x 2	Nominal Power (RMS) Output at 4 ff	60W x 2
Nominal Power (RMS) Output - Bridged at 4 ff	190W x 1	Frequency Response	10Hz ~ 70kHz
Total Harmonic Distortion (THD)	<0.05 %	Signal-to-Noise (SN) Ratio	>95 dB
Fuse Rating	25A		

SPECIFICATIONS			
RCA Inputs	2-Ch.	Speaker Level Inputs	✔
Crossover Type	LPF	Low-Pass Crossover Frequency	80Hz
Low Pass Slope (dB/octave)	-12db/oct	Automatic Signal Sensing and Turn-On	✔
Hi-Volt Input Level Control	0.3V to 6.5V (RCA in), 3.0V to 26V (SP in)	Terminal Type	Screw-Type Terminal
Load Impedance Allowance (Ω)	2 to 4	Bridgeable	✔
Protection Control System	✔	Dimensions (WxHxD)(inches)	246(W) X 60(H) X 180(D) mm
Warranty	1 Year		