

Monitor Section	Picture size	6.75inches(diagonal) wide
	W x H	151.8 x 79.7mm, 5-15/16 x 3-1/8 inch
	Display system	Transparent TN LCD panel
	Drive system	TFT active matrix system
	Number of pixels	1,152,000
		800H x 480V x RGB
	Effective pixels	99.99%
	Pixel arrangement	RGB striped arrangement
	Back lighting	LED
USB I/F Section	USB Standard	USB2.0 High Speed
	File System	FAT 16/32 , exFAT
	Maximum Power Supply Current	DC5V=1.5A
	D/A Converter	24Bit
	Audio Decoder	MP3 / WMA / AAC / WAV / FLAC
	Video Decoder	MPEG1/2,MPEG4 / WMV / H.264 / .mkv
	Frequency response 192k Sampling	20 - 20,000 Hz
	96k Sampling	20 - 20,000 Hz
	48k Sampling	20 - 20,000 Hz
	44.1k Sampling	20 - 20,000 Hz
	Total harmonic distortion 1kHz	0.2
	Signal to Noise ratio	75dB
	Dynamic range	75dB
Technology	Bluetooth Ver4.1	
	Frequency	2.402 – 2.480 GHz

Monitor Section	Picture size	6.75inches(diagonal) wide
	W x H	151.8 x 79.7mm, 5-15/16 x 3-1/8 inch
	Display system	Transparent TN LCD panel
	Drive system	TFT active matrix system
	Number of pixels	1,152,000
		800H x 480V x RGB
	Effective pixels	99.99%
	Pixel arrangement	RGB striped arrangement
	Back lighting	LED
USB I/F Section	USB Standard	USB2.0 High Speed
	File System	FAT 16/32 , exFAT
	Maximum Power Supply Current	DC5V=1.5A
	D/A Converter	24Bit
	Audio Decoder	MP3 / WMA / AAC / WAV / FLAC
	Video Decoder	MPEG1/2,MPEG4 / WMV / H.264 / .mkv
	Frequency response 192k Sampling	20 - 20,000 Hz
	96k Sampling	20 - 20,000 Hz
	48k Sampling	20 - 20,000 Hz
	44.1k Sampling	20 - 20,000 Hz
	Total harmonic distortion 1kHz	0.2
	Signal to Noise ratio	75dB
	Dynamic range	75dB
Technology	Bluetooth Ver4.1	
	Frequency	2.402 – 2.480 GHz

Monitor Section	Picture size	6.75inches(diagonal) wide
	W x H	151.8 x 79.7mm, 5-15/16 x 3-1/8 inch
	Display system	Transparent TN LCD panel
	Drive system	TFT active matrix system
	Number of pixels	1,152,000
		800H x 480V x RGB
	Effective pixels	99.99%
	Pixel arrangement	RGB striped arrangement
	Back lighting	LED
USB I/F Section	USB Standard	USB2.0 High Speed
	File System	FAT 16/32 , exFAT
	Maximum Power Supply Current	DC5V=1.5A
	D/A Converter	24Bit
	Audio Decoder	MP3 / WMA / AAC / WAV / FLAC
	Video Decoder	MPEG1/2, MPEG4 / WMV / H.264 / .mkv
	Frequency response 192k Sampling	20 - 20,000 Hz
	96k Sampling	20 - 20,000 Hz
	48k Sampling	20 - 20,000 Hz
	44.1k Sampling	20 - 20,000 Hz
	Total harmonic distortion 1kHz	0.2
	Signal to Noise ratio	75dB
	Dynamic range	75dB
Technology	Bluetooth Ver4.1	
	Frequency	2.402 – 2.480 GHz

Monitor Section	Picture size	6.75inches(diagonal) wide
	W x H	151.8 x 79.7mm, 5-15/16 x 3-1/8 inch
	Display system	Transparent TN LCD panel
	Drive system	TFT active matrix system
	Number of pixels	1,152,000
		800H x 480V x RGB
	Effective pixels	99.99%
	Pixel arrangement	RGB striped arrangement
	Back lighting	LED
USB I/F Section	USB Standard	USB2.0 High Speed
	File System	FAT 16/32 , exFAT
	Maximum Power Supply Current	DC5V=1.5A
	D/A Converter	24Bit
	Audio Decoder	MP3 / WMA / AAC / WAV / FLAC
	Video Decoder	MPEG1/2,MPEG4 / WMV / H.264 / .mkv
	Frequency response 192k Sampling	20 - 20,000 Hz
	96k Sampling	20 - 20,000 Hz
	48k Sampling	20 - 20,000 Hz
	44.1k Sampling	20 - 20,000 Hz
	Total harmonic distortion 1kHz	0.2
	Signal to Noise ratio	75dB
	Dynamic range	75dB
Technology	Bluetooth Ver4.1	
	Frequency	2.402 – 2.480 GHz

Monitor Section	Picture size	6.75inches(diagonal) wide
	W x H	151.8 x 79.7mm, 5-15/16 x 3-1/8 inch
	Display system	Transparent TN LCD panel
	Drive system	TFT active matrix system
	Number of pixels	1,152,000
		800H x 480V x RGB
	Effective pixels	99.99%
	Pixel arrangement	RGB striped arrangement
	Back lighting	LED
USB I/F Section	USB Standard	USB2.0 High Speed
	File System	FAT 16/32 , exFAT
	Maximum Power Supply Current	DC5V=1.5A
	D/A Converter	24Bit
	Audio Decoder	MP3 / WMA / AAC / WAV / FLAC
	Video Decoder	MPEG1/2,MPEG4 / WMV / H.264 / .mkv
	Frequency response 192k Sampling	20 - 20,000 Hz
	96k Sampling	20 - 20,000 Hz
	48k Sampling	20 - 20,000 Hz
	44.1k Sampling	20 - 20,000 Hz
	Total harmonic distortion 1kHz	0.2
	Signal to Noise ratio	75dB
Dynamic range	75dB	
Technology	Bluetooth Ver4.1	
	Frequency	2.402 – 2.480 GHz

Monitor Section	Picture size	6.75inches(diagonal) wide
	W x H	151.8 x 79.7mm, 5-15/16 x 3-1/8 inch
	Display system	Transparent TN LCD panel
	Drive system	TFT active matrix system
	Number of pixels	1,152,000
		800H x 480V x RGB
	Effective pixels	99.99%
	Pixel arrangement	RGB striped arrangement
	Back lighting	LED
USB I/F Section	USB Standard	USB2.0 High Speed
	File System	FAT 16/32 , exFAT
	Maximum Power Supply Current	DC5V=1.5A
	D/A Converter	24Bit
	Audio Decoder	MP3 / WMA / AAC / WAV / FLAC
	Video Decoder	MPEG1/2,MPEG4 / WMV / H.264 / .mkv
	Frequency response 192k Sampling	20 - 20,000 Hz
	96k Sampling	20 - 20,000 Hz
	48k Sampling	20 - 20,000 Hz
	44.1k Sampling	20 - 20,000 Hz
	Total harmonic distortion 1kHz	0.2
	Signal to Noise ratio	75dB
	Dynamic range	75dB
Technology	Bluetooth Ver4.1	
	Frequency	2.402 – 2.480 GHz