

DVD Section

CS

D/A Converter		24 / 32Bit
Audio Decoder		Linear PCM Dolby Audio MP3 / WMA / AAC / WAV / FLAC / Vorbis
Video Decoder		MPEG1/2,MPEG4 / WMV / H.264 / MKV
Wow & Flutter		Below Measurable Limit
Frequency response	96k Sampling	20 - 44,000 Hz
	48k Sampling	20 - 22,000 Hz
	44.1k Sampling	20 - 20,000 Hz
Total harmonic distortion 1kHz		0.010%
Signal to Noise ratio		90.5dB (DVD-Video 96k)
Dynamic range		89dB (DVD-Video 96k)
DISC Format		DVD-Video / VIDEO-CD / CD-DA
Quantifying bit number		16 / 20 / 24bit

USB I/F Section

USB Standard		USB2.0 High Speed
File System		FAT 16/32, exFAT, NTFS
Maximum Power Supply Current		DC5V=1.5A
D/A Converter		24/32Bit
Audio Decoder		MP3 / WMA / AAC / WAV / FLAC / Vorbis
Video Decoder		MPEG1/2,MPEG4 / WMV / H.264 / MKV

Wireless Mirroring Section

Mode		Sink
Copyright protection		HDCP2.2
Touch Control		UIBC

Wi-Fi

IEEE Standard		802.11 a/b/g/n/ac
Frequency Range		Dual Band (2.4GHz / 5GHz)
Channels	Auto(1-11ch)	
	Auto(149,153,157,161ch)	
Transfer rates (MAX)	11a: 54 Mbps / 11b: 11 Mbps /	
	11g: 54 Mbps / 11n: 300 Mbps /	
	11ac: 867 Mbps	
Output Power	2.4GHz/SISO	11b:14dBm±2dB / 11g:13dBm±2dB /
		11n(20MHz):12dBm±2dB
		11a:9dBm+2dB /

DVD Section

D/A Converter		24 / 32Bit
Audio Decoder		Linear PCM Dolby Audio MP3 / WMA / AAC / WAV / FLAC / Vorbis
Video Decoder		MPEG1/2,MPEG4 / WMV / H.264 / MKV
Wow & Flutter		Below Measurable Limit
Frequency response	96k Sampling	20 - 44,000 Hz
	48k Sampling	20 - 22,000 Hz
	44.1k Sampling	20 - 20,000 Hz
Total harmonic distortion 1kHz		0.010%
Signal to Noise ratio		90.5dB (DVD-Video 96k)
Dynamic range		89dB (DVD-Video 96k)
DISC Format		DVD-Video / VIDEO-CD / CD-DA
Quantifying bit number		16 / 20 / 24bit

USB I/F Section

USB Standard		USB2.0 High Speed
File System		FAT 16/32, exFAT, NTFS
Maximum Power Supply Current		DC5V=1.5A
D/A Converter		24/32Bit
Audio Decoder		MP3 / WMA / AAC / WAV / FLAC / Vorbis
Video Decoder		MPEG1/2,MPEG4 / WMV / H.264 / MKV

Wireless Mirroring Section

Mode		Sink
Copyright protection		HDCP2.2
Touch Control		UIBC

Wi-Fi

IEEE Standard		802.11 a/b/g/n/ac
Frequency Range		Dual Band (2.4GHz / 5GHz)
Channels		Auto(1-11ch)
		Auto(149,153,157,161ch)
Transfer rates (MAX)		11a: 54 Mbps / 11b: 11 Mbps /
		11g: 54 Mbps / 11n: 300 Mbps /
		11ac: 867 Mbps
Output Power	2.4GHz/SISO	11b:14dBm±2dB / 11g:13dBm±2dB /
		11n(20MHz):12dBm±2dB
		11a:9dBm+2dB /

DVD Section

CS

D/A Converter		24 / 32Bit
Audio Decoder		Linear PCM Dolby Audio MP3 / WMA / AAC / WAV / FLAC / Vorbis
Video Decoder		MPEG1/2,MPEG4 / WMV / H.264 / MKV
Wow & Flutter		Below Measurable Limit
Frequency response	96k Sampling	20 - 44,000 Hz
	48k Sampling	20 - 22,000 Hz
	44.1k Sampling	20 - 20,000 Hz
Total harmonic distortion 1kHz		0.010%
Signal to Noise ratio		90.5dB (DVD-Video 96k)
Dynamic range		89dB (DVD-Video 96k)
DISC Format		DVD-Video / VIDEO-CD / CD-DA
Quantifying bit number		16 / 20 / 24bit

USB I/F Section

USB Standard		USB2.0 High Speed
File System		FAT 16/32, exFAT, NTFS
Maximum Power Supply Current		DC5V=1.5A
D/A Converter		24/32Bit
Audio Decoder		MP3 / WMA / AAC / WAV / FLAC / Vorbis
Video Decoder		MPEG1/2,MPEG4 / WMV / H.264 / MKV

Wireless Mirroring Section

Mode		Sink
Copyright protection		HDCP2.2
Touch Control		UIBC

Wi-Fi

IEEE Standard		802.11 a/b/g/n/ac
Frequency Range		Dual Band (2.4GHz / 5GHz)
Channels		Auto(1-11ch)
		Auto(149,153,157,161ch)
Transfer rates (MAX)		11a: 54 Mbps / 11b: 11 Mbps /
		11g: 54 Mbps / 11n: 300 Mbps /
		11ac: 867 Mbps
Output Power	2.4GHz/SISO	11b:14dBm±2dB / 11g:13dBm±2dB /
		11n(20MHz):12dBm±2dB
		11a:9dBm+2dB /

DVD Section

CS

D/A Converter		24 / 32Bit
Audio Decoder		Linear PCM Dolby Audio MP3 / WMA / AAC / WAV / FLAC / Vorbis
Video Decoder		MPEG1/2,MPEG4 / WMV / H.264 / MKV
Wow & Flutter		Below Measurable Limit
Frequency response	96k Sampling	20 - 44,000 Hz
	48k Sampling	20 - 22,000 Hz
	44.1k Sampling	20 - 20,000 Hz
Total harmonic distortion 1kHz		0.010%
Signal to Noise ratio		90.5dB (DVD-Video 96k)
Dynamic range		89dB (DVD-Video 96k)
DISC Format		DVD-Video / VIDEO-CD / CD-DA
Quantifying bit number		16 / 20 / 24bit

USB I/F Section

USB Standard		USB2.0 High Speed
File System		FAT 16/32, exFAT, NTFS
Maximum Power Supply Current		DC5V=1.5A
D/A Converter		24/32Bit
Audio Decoder		MP3 / WMA / AAC / WAV / FLAC / Vorbis
Video Decoder		MPEG1/2,MPEG4 / WMV / H.264 / MKV

Wireless Mirroring Section

Mode		Sink
Copyright protection		HDCP2.2
Touch Control		UIBC

Wi-Fi

IEEE Standard		802.11 a/b/g/n/ac
Frequency Range		Dual Band (2.4GHz / 5GHz)
Channels		Auto(1-11ch)
		Auto(149,153,157,161ch)
Transfer rates (MAX)		11a: 54 Mbps / 11b: 11 Mbps /
		11g: 54 Mbps / 11n: 300 Mbps /
		11ac: 867 Mbps
Output Power	2.4GHz/SISO	11b:14dBm±2dB / 11g:13dBm±2dB /
		11n(20MHz):12dBm±2dB
		11a:9dBm+2dB /

DVD Section

CS

D/A Converter		24 / 32Bit
Audio Decoder		Linear PCM Dolby Audio MP3 / WMA / AAC / WAV / FLAC / Vorbis
Video Decoder		MPEG1/2,MPEG4 / WMV / H.264 / MKV
Wow & Flutter		Below Measurable Limit
Frequency response	96k Sampling	20 - 44,000 Hz
	48k Sampling	20 - 22,000 Hz
	44.1k Sampling	20 - 20,000 Hz
Total harmonic distortion 1kHz		0.010%
Signal to Noise ratio		90.5dB (DVD-Video 96k)
Dynamic range		89dB (DVD-Video 96k)
DISC Format		DVD-Video / VIDEO-CD / CD-DA
Quantifying bit number		16 / 20 / 24bit

USB I/F Section

USB Standard		USB2.0 High Speed
File System		FAT 16/32, exFAT, NTFS
Maximum Power Supply Current		DC5V=1.5A
D/A Converter		24/32Bit
Audio Decoder		MP3 / WMA / AAC / WAV / FLAC / Vorbis
Video Decoder		MPEG1/2,MPEG4 / WMV / H.264 / MKV

Wireless Mirroring Section

Mode		Sink
Copyright protection		HDCP2.2
Touch Control		UIBC

Wi-Fi

IEEE Standard		802.11 a/b/g/n/ac
Frequency Range		Dual Band (2.4GHz / 5GHz)
Channels		Auto(1-11ch)
		Auto(149,153,157,161ch)
Transfer rates (MAX)		11a: 54 Mbps / 11b: 11 Mbps /
		11g: 54 Mbps / 11n: 300 Mbps /
		11ac: 867 Mbps
Output Power	2.4GHz/SISO	11b:14dBm±2dB / 11g:13dBm±2dB /
		11n(20MHz):12dBm±2dB
		11a:9dBm+2dB /

DVD Section

3CS

D/A Converter		24 / 32Bit
Audio Decoder		Linear PCM Dolby Audio MP3 / WMA / AAC / WAV / FLAC / Vorbis
Video Decoder		MPEG1/2,MPEG4 / WMV / H.264 / MKV
Wow & Flutter		Below Measurable Limit
Frequency response	96k Sampling	20 - 44,000 Hz
	48k Sampling	20 - 22,000 Hz
	44.1k Sampling	20 - 20,000 Hz
Total harmonic distortion 1kHz		0.010%
Signal to Noise ratio		90.5dB (DVD-Video 96k)
Dynamic range		89dB (DVD-Video 96k)
DISC Format		DVD-Video / VIDEO-CD / CD-DA
Quantifying bit number		16 / 20 / 24bit

USB I/F Section

USB Standard		USB2.0 High Speed
File System		FAT 16/32, exFAT, NTFS
Maximum Power Supply Current		DC5V=1.5A
D/A Converter		24/32Bit
Audio Decoder		MP3 / WMA / AAC / WAV / FLAC / Vorbis
Video Decoder		MPEG1/2,MPEG4 / WMV / H.264 / MKV

Wireless Mirroring Section

Mode		Sink
Copyright protection		HDCP2.2
Touch Control		UIBC

Wi-Fi

IEEE Standard		802.11 a/b/g/n/ac
Frequency Range		Dual Band (2.4GHz / 5GHz)
Channels		Auto(1-11ch)
		Auto(149,153,157,161ch)
Transfer rates (MAX)		11a: 54 Mbps / 11b: 11 Mbps /
		11g: 54 Mbps / 11n: 300 Mbps /
		11ac: 867 Mbps
Output Power	2.4GHz/SISO	11b:14dBm±2dB / 11g:13dBm±2dB /
		11n(20MHz):12dBm±2dB
		11a:9dBm+2dB /