

H 7780 BP2 30" Convection Double Oven - ContourLine

Features:

- M-Touch Display with Motion React Simple to use touch controls
- Miele@Home Control the appliances with your app
- Roast Probe For Precision cooking
- Moisture Plus a burst of steam for professional quality cooking results at home
- Direct Water No need to fill any water tanks
- Taste Control Prevents overcooked dishes

Included:

- 1 Perforated baking tray
- 2 Universal baking tray
- 4 Self Clean Ready Baking and Roasting Racks
- 2 Self Clean Ready Rack with rail system

MATERIAL

11805570

SPECIFICATIONS	
Overall Unit Dimensions	29 ^{13/16} " (757 mm) W x 51 ¹ /2" (1308 mm) H x 23 ³ /4" (603 mm) D
Niche	
Minimum Cabinet Niche Opening	28¹/₂" (724 mm) W x 51¹/₀" (1299 mm) H x 24" (610 mm) D
Plumbing	
Water Supply Requirements	 Cold water connection Male 3/8" compression fitting Water pressure range 14.5 psi (1 bar) and 145 psi (10 bar)
Water Connection Line (Supplied)	Length: 5 ft (1.5 m) Female 3/8" compression.
Electrical	
Electrical Requirements	120/208-240V, 60Hz, 50 Amps
Power Cord	NEMA 14-50 plug, 5 ft (1.52 m)
Shipping	
Shipping Weight	379 lbs (172 kg)
Shipping Dimensions	307/16" (776 mm) W x 58 ⁵ 84" (1490 mm) H x 32 ^{15/16} " (836 mm) D

PRODUCT DIMENSIONS







FLUSH CUTOUT DIMENSIONS





- A Cut-out (4" x 28" [100 mm x 720 mm]) in the bottom of the cabinet for the power cord and Ventilation
- I)- Electrical and water supplies are recommended to be placed in adjacent cabinetry.
 Additional cabinet depth is required when placing the electrical and water supplies behind the appliance.



PROUD CUTOUT DIMENSIONS



- A Cut-out (4" x 28" [100 mm x 720 mm]) in the bottom of the cabinet for the power cord and Ventilation
- Electrical and water supplies are recommended to be placed in adjacent cabinetry.
 Additional cabinet depth is required when placing the electrical and water supplies behind the appliance.