

SPECIFICATIONS

INPUTS

Inputs: 8 Balanced Inputs, 8 Unbalanced RCA Inputs, 2 Digital Combo Coax/Toslink Inputs
Input Sensitivity: 1 Vrms for full output, level at maximum
Input Gain: 30 dB

OUTPUTS

Amplifier Channels: 3
Power Output (70 V / 100 V): 750W per channel
Power Output (70 V / 100 V Bridged Mono): 1500W
Power Output (8 Ω): 500W per channel
Power Output (2 Ω / 4 Ω): 750W per channel
Power Output (4 Ω / 8 Ω Bridged Mono): 1500W
Minimum Speaker Load: 2 Ω
Preamp Audio Outputs: 4 Balanced, 4 Unbalanced RCA, 4 Digital Coax Loop Outputs

CONTROL

Remote Power Trigger: +12 VDC or Dry Contact Closure
Network Connection/Protocol: 10BaseT Ethernet TCP/IP
Communication Protocol: HTTP or Telnet

WEIGHTS & DIMENSIONS

Dimensions: 17" W x 15.5" D x 3.5" H (2U)
Weight: 18.5 lbs (8.4 kg)

IN THE BOX: Model CM3-750, Speaker Connectors, Remote Connector, Power Cord, Manual, Warranty