DMP-A6G2 Specifications

Basic Parameters

Model
EVERSOLO DMP-A6 Gen 2

Display
6-inch LCD Touchscreen

Internal Memory
4GDDR4 +32G eMMC

DAC
ES 9038Q2M*2

Op-amp Chip
OPA1642

Power Supply
Low Noise, High-Quality Linear Power Supply

Built-in SSD Slot
M.2 NVME 3.0 2280 Interface Protocol, Supports up to 8TB

USB-A Ports
USB3.0*2

Ethernet
RJ-45 (10/100/1000Mbps)

Wireless Network
WiFi 2.4G+5G Dual-Band

Music Playback and DAC Decoding
Supports up to Stereo DSD512, PCM 768KHz 32Bit, MQA Format

Music Services
TIDAL, Qobuz, HIGHRESAUDIO, Amazon Music, IDAGIO, Calm Radio, Internet Radio, TuneIn, Radio Paradise, Deezer, SoundCloud, Presto Music, Apple Music*...

Network Protocol
WebDAV, UPnP, NFS, SMB, Onedrive, Drop box, emby, Plex...

Streaming
Roon Ready, Spotify Connect, DLNA, TIDAL Connect...

Control Methods
Mobile App Control, Touchscreen Control, Tablet App Control,TRIGGER OUT,WOL

Audio Input and Output

Bluetooth Audio Input
Bluetooth BT5.0, Supports SBC/AAC

USB-B Audio Input
USB Audio Compatibility: Windows (10, 11), Mac, Android, iOS
Supports up to Stereo DSD512, PCM 768KHz 32Bit, MQA Format

Optical/Coaxial Audio Input
Supports up to Stereo PCM 192KHz 24Bit, Dop64, MQA Format

HDMI ARC Input
Supports up to Stereo PCM 192KHz/24Bit

USB Audio Output
Supports up to Stereo DSD512 Native, PCM 768KHz 32Bit, MQA Format

HDMI Audio Output
DSD64 Native multichannel/PCM 192KHz multichannel raw output,up to 5.1

Optical/Coaxial Audio Output
Supports up to Stereo PCM 192KHz 24Bit, Dop64, MQA Format

Analog Audio Output
Pre-output: XLR (Balanced) + RCA(UnBalanced)

Audio Characteristics
XLR Output Audio Characteristics
Output Level: 5.2V
Frequency Response: 20Hz~20KHz (±0.15dB)
Dynamic Range: >128dB
SNR: >128dB @A-wt
THD+N: <0.00009% (-120dB)
Crosstalk: >-125dB

RCA Output Audio Characteristics
Output Level: 2.6V
Frequency Response: 20Hz~20KHz (±0.2dB)
Dynamic Range: >124dB
SNR: >124dB @A-wt
THD+N: <0.00011% (-119dB)
Crosstalk: >-124dB

Other Information

PSU
AC 110~240V 50/60Hz Max 0.35A

Rated Power
13W

Dimensions
L 187mm * W 270mm * H 90mm

Packing List
Power Cable*1, USB Data Cable*1, Trigger Cable*1, User Manual*1