FRIGIDAIRE GALLERY

French Door Refrigerators

FGHB2866P F/P/E

28 Cu. Ft. Standard-Depth

Product Dimensions

Height (Including Hinges & Rollers)	69-7/8"
Width (Doors)	36"
Depth (Including Door)	33-3/8"

More Easy-To-Use Features

Multi-Level LED Lighting
Corner-to-corner LED lighting throughout the refrigerator for better visibility.

Full-Width Cool Zone™ Drawer
A large capacity Cool Zone™ Drawer extends completely and provides space to easily store anything from sheet cakes and large platters to snacks and juice boxes.

LCD Express-Select® Controls on Ice and Water Dispenser
Easily select options with the touch of a button.

Freezer Basket with Divider
Deep freezer storage with adjustable divider keeps food organized and accessible.

Dual Ice Ready
Be ready for any occasion with an option for a second ice maker.

Quick Freeze
Quickly freeze foods so they stay at their freshest.

Effortless™ Glide Crisper Drawers
Our humidity-controlled crisper drawers can be configured any number of ways, either side-by-side or stacked on top of each other so you can organize your refrigerator the way you want, while keeping your fruits and vegetables fresh.

Effortless™ Glide Freezer Drawers
Drawers glide out smoothly and fully extend, giving you easy access to what's inside.

ENERGY STAR®
Sabbath Mode (Star-K® Certified)

Signature Features

Adjustable Interior Storage
Over 100 ways to organize and customize your refrigerator.

SpillSafe® Flip-Up & Slide-Under Shelves
Easily make room for tall or large items with the new Flip-Up and Slide-Under Shelves.

Best-in-Class Ice & Water Filtration[1]
PureSource Ultra® Water Filtration offers best-in-class water filtration so you get cleaner, fresher ice and water for your family.

Smudge-Proof™ Stainless Steel[2]
Resists fingerprints and smudges and is easy to clean.

Available in:

Stainless (F)	Pearl (P)	Ebony (E)

[1]As compared to other consumer refrigeration water filtration systems.
[2]Select models only.

frigidaire.com

Features	
Door Design	Soft-Arc Doors
Door Handle Design	SS (F) / Color-C. (P/E)
Cabinet Finish	Grey (F) / Color-C. (P/E)
Door Stops / Door Closers	Yes / Yes
Door Hinge Covers	Hidden
Rollers – Front / Rear	Adjustable / Yes
Energy Saver Plus Technology	Yes
Water Filter Location	Top-Right Fresh Food Section
Sound Package	Quiet Pack
Dispenser	
Controls	Express-Select®
Dispenser Design	Flush, Single-Paddle
Number of Dispenser Buttons	11
Crushed Ice / Cube Ice / Water	Yes / Yes / Yes
Ice Option / Freeze Option	No / Quick Freeze
Display On / Off Option	Yes
Lock / Light	Yes / Yes
Temp / Door Ajar / Power Failure Alerts	
Water Filter Change Indicator Light	Yes
Air Filter Change Indicator Light	Yes
Refrigerator Features	
Lighting	Multi-Level LED
Water Filter Type	PureSource Ultra®
Air Filter Type	PureAir Ultra®
Quarter-Width Fixed Shelves	1 SpillSafe® Flip-Up
Half-Width Fixed Shelves	1 SpillSafe® Slide-Under
Quarter-Width Sliding Shelves	
Half-Width Sliding Shelves	2 SpillSafe®
Cantilever Shelves	Yes
Store-More™ Full-Width Drawer	1 Cool Zone™
Hanging Wine Rack / Can Dispenser	1 White / No
Crisper Drawer / Humidity Controls	2 Clear / 2
Dairy Compartment	1 Clear
Store-More™ Fixed Door Bins	2 White (1 per door)
2-Liter Fixed Door Bins	1 Clear
Gallon Adjustable Door Bins	2 Clear
2-Liter Adjustable Door Bins	
Dispenser Bin	1
Non-Slip Bin Liner / Bottle Retainers	
Freezer Features	
Self-Closing Pull-Out Drawer	Yes
Sliding Full-Width Freezer Baskets	2 Effortless™ Glide
Basket Dividers	1 (Bottom Basket)
Lighting	LED
Automatic Ice Maker (2nd Ice Maker)	Optional (PN#IMK0028A)
Certifications	
Sabbath Mode (Star-K® Certified)	Yes
ENERGY STAR®	Yes
Specifications	
Total Capacity (Cu. Ft.)	27.19
Refrigerator Capacity (Cu. Ft.)	18.48
Freezer Capacity (Cu. Ft.)	8.71
Power Supply Connection Location	Right Bottom Rear
Water Inlet Connection Location	Left Bottom Rear
Voltage Rating	120V / 60Hz / 15 or 20A
Connected Load (kW rating) @ 120 Volts[1]	1.02
Amps @ 120 Volts	8.5
Minimum Circuit Required (Amps)	15
Shipping Weight (Approx.)	365 Lbs.

[1]*For use on adequately wired 120V, dedicated circuit having 2-wire service with a separate ground wire. Appliance must be grounded for safe operation.*

Standard Refrigerator Depth vs. Counter Depth

Counter Depth
23⁷⁄₈"

28³⁄₄"
Standard Depth

Top View

Recessed water line

Recessed electrical outlet

Allow 1" min. clearance at rear for proper air circulation and water / electrical connections

24" Cabinet

25" Countertop

28⁷⁄₈" Side Panels, ¹⁄₂" min. width

NOTE: For planning purposes only. Always consult local and national electric and plumbing codes. Refer to Product Installation Guide for detailed installation instructions on the web at frigidaire.com.

Product Dimensions	
A - Height (Incl. Hinges & Rollers)	69-7/8"
B - Cabinet Width / Door Width	35-7/8" / 36"
C - Depth (Incl. Door)	33-3/8"
Depth with Door Open 90°	47-3/8"
Depth with Drawer Fully Extended (Incl. Handle)	55"

Specifications subject to change.

Standard Refrigerator Depth vs. Counter Depth

Counter Depth
23 7/8"

28 3/4"
Standard Depth

**"Built-In Look"
Cutout Dimensions**

(A) 70 1/4"   (B) 36"   (C) 28 7/8"

33 3/8"

35 7/8"
Cabinet

36"
Doors

5"

69 7/8"
with
3/8"
rollers

68 5/8"
with
3/8"
rollers

Water line inlet location (left bottom rear)

Power cord location (right bottom rear)

28 3/4"

35 7/8"

55"
(with drawer fully extended including handle)

47 3/8" (with doors 90° open)

Top View

Recessed water line

Recessed electrical outlet

Allow 1" min. clearance at rear for proper air circulation and water/electrical connections

24"
Cabinet

25"
Countertop

28 7/8" Side Panels, 1/2" min. width

French Door Refrigerator Specifications

- Product Shipping Weight (approx.) – 365 Lbs.
- An electrical supply with grounded three-prong receptacle is required. The power supply circuit must be installed in accordance with current edition of National Electrical Code (NFPA 70) and local codes & ordinances.
- Voltage Rating – 120V/60 Hz/15 or 20 Amps
- Connected Load (kW Rating) @120 Volts = 1.02 kW
- Amps @ 120 Volts = 8.5 Amps
- Always consult local and national electric & plumbing codes.
- Floor should be level surface of hard material, capable of supporting fully loaded refrigerator.
- When installing refrigerator adjacent to wall, cabinet or other appliance that extends beyond front edge of unit, 20" minimum clearance recommended to allow for optimum 120° to 180° door swing, providing complete drawer/crisper access and removal. *(Absolute 4-1/2" minimum clearance will ONLY allow for 90° door swing which will provide drawer/crisper access with restricted removal.)*
- To ensure optimum performance, avoid installing in direct sunlight or close proximity to range, dishwasher or other heat source.
- For proper ventilation, front grille MUST remain unobstructed.

- Recess electrical outlet when possible.
- Water recess on rear wall recommended to prevent water line damage.
- Water Pressure – Cold water line must provide between 30 and 100 pounds per square inch (psi).
- Copper tubing with 1/4" O.D. recommended for water supply line with length equal to distance from rear of unit to household water supply line plus 7 additional feet. Optional Water Supply Installation Kits available.
- Adjustable front rollers to assist with door alignment.

"Built-In Look" Specifications

- Minimum opening of 70-1/4" H x 36" W x 28-7/8" D required to allow for ease of installation, proper air circulation, and plumbing/electrical connections.
- Remove all wall/floor molding prior to installation.

Note: For planning purposes only. Refer to Product Installation Guide on the web at frigidaire.com for detailed instructions.

Optional Accessories

- Second Ice Maker Kit – (PN # IMK0028A)

Specifications subject to change.