

# UNDER-COUNTER BEVERAGE CENTERS

EI24BC10QS (RIGHT DOOR SWING)  
EI24BL10QS (LEFT DOOR SWING)

Featuring IQ-Touch™ Electronic Controls



## PRODUCT DIMENSIONS

Height	33-3/4"
Width	23-7/8"
Depth (Including Handle)	26"

## MORE EASY-TO-USE FEATURES

### MULTIPLE STORAGE OPTIONS

A display rack and two fully extendable glass shelves provide maximum versatility.

### UV FILTERED GLASS DOOR

Helps protect wine's flavor from deterioration caused by harmful UV-rays.

### PUREADVANTAGE® AIR FILTRATION

Keeps air fresh by circulating fresh, clean air throughout.

### PLATINUM STAR® LIMITED WARRANTY

Our exclusive limited warranty that includes a 3-year coverage on parts and one year on labor without charge<sup>1</sup>.

### VERSATILE INSTALLATION OPTIONS

Models are available in either right or left swing — making placement easier.

### REFRIGERATOR ALARM SYSTEM

Notifies you if there's been a power failure, if a door stays open longer than five minutes and if the interior temperature of the beverage center exceeds 10 degrees from set-point for more than 60 minutes.

### A.D.A. COMPLIANT

When properly installed, this model is A.D.A.-qualified based on the United States Access Board's A.D.A./A.B.A. Accessibility Guidelines and the Department of Justice's 2010 A.D.A. Standards for Accessible Design.

### ENERGY STAR®

Available in:



Stainless  
(S)

<sup>1</sup>Eligibility based on product registration with Electrolux North America within 60 days of purchase. Products must have been purchased on or after July 1, 2013. Coverage includes material parts for 3 years and labor for 1 year.

## SIGNATURE FEATURES



### PERFECT SET® TEMPERATURE CONTROL

Chill your beverage to the ideal serving temperature with the Perfect Set® temperature control anywhere between 34 and 42 °F.



### LUXURY-GLIDE® SHELVES

With a ball bearing system, shelves are so smooth they extend effortlessly.



### LUXURY-DESIGN® LED LIGHTING

Lighting is as beautiful as it is functional, keeping your beverages and wine clearly visible. In display mode, the lights can stay on to display your wine collection.



### INTEGRATED CONTROLS

Controls are located on the top of the door — so they're easy to set when needed, and hidden from view when the door is closed.

# UNDER-COUNTER BEVERAGE CENTERS



EI24BC10QS (RIGHT DOOR SWING)  
EI24BL10QS (LEFT DOOR SWING)

## 24" UNDER-COUNTER BEVERAGE CENTERS

Capacity	5.4 Cu.Ft.
Installation Type	Built-In / Freestanding

### FEATURES

iQ-Touch™ Electronic Controls	Yes
Fully Integrated Control Panel	Yes
Blue LED Display	Yes
Luxury-Glide® 3/4-Extension Glass Shelves	2
Half-Width Fixed Shelf	1
Lower Level Display Rack	Yes
Silver Metallic Trim on Racks	Yes
Luxury-Design® LED Lighting	Yes
Exhibit Lighting	Yes
Perfect Set® Controls	Yes
PureAdvantage® Air Filtration	Yes
Electronic Control Lock	Yes
Display Temp Mode (°C or °F)	Yes
Door Ajar Acoustic Alarm	Yes
High-Temperature Acoustic Alarm	Yes
Power Failure Acoustic Alarm	Yes
Power-On/Off Control	Yes
Vacation Mode	Yes
Sabbath Mode (Star-K® Certified)	Yes
Frost-Free Performance	Yes
Dynamic Condenser	Yes
ENERGY STAR®	Yes

### ADDITIONAL FEATURES

UV-Filtered, Tinted Glass Window	Yes
Luxury-Close™ Door	Yes
Adjustable Leveling Legs	4
A.D.A. Compliant*	Yes

### ACCESSORIES

PureAdvantage® Replacement Air Filter – PN# EAFCBF	Included
--	----------

### SPECIFICATIONS


Color –	
Stainless Steel	S
Temperature Range	34°F – 42°F
Power Supply Connection Location	Right Bottom Rear
Voltage Rating	115V / 60 Hz
Connected Load (kW Rating) @ 115 Volts†	0.15
Minimum Circuit Required (Amps)	15A
Shipping Weight (Approx.)	128 Lbs.

\*When properly installed, this model is A.D.A.-qualified based on the United States Access Board's A.D.A./A.B.A. Accessibility Guidelines and the Department of Justice's 2010 A.D.A. Standards for Accessible Design.

†For use on adequately wired 120V, dedicated circuit having 2-wire service with a separate ground wire. Appliance must be grounded for safe operation.

NOTE: Always consult local and national electric codes. Refer to Product Installation Guide for detailed installation instructions on the web at [electroluxappliances.com](http://electroluxappliances.com).

Specifications subject to change.



### PRODUCT DIMENSIONS

Height	33-3/4"
Width	23-7/8"
Depth (Including Handle) (with Door 90° Open)	26" 46-13/32"

## Electrolux Major Appliances, N.A.

USA • 10200 David Taylor Drive • Charlotte, NC 28262 • 1-877-4electrolux (1-877-435-3287) • [electroluxappliances.com](http://electroluxappliances.com)  
CANADA • 5855 Terry Fox Way • Mississauga, ON L5V 3E4 • 1-800-265-8352 • [electroluxappliances.ca](http://electroluxappliances.ca)

EI24BC10Q 08/16

© 2016 Electrolux Home Products, Inc.




High standards of quality at Electrolux Home Products, Inc. mean we are constantly working to improve our products. We reserve the right to change specifications or discontinue models without notice.

# UNDER-COUNTER BEVERAGE CENTERS



EI24BC10QS (RIGHT DOOR SWING)  
EI24BL10QS (LEFT DOOR SWING)



## Under-Counter Beverage Center Specifications

- Product Weight – 118 Lbs.
- Voltage Rating – 115V/60Hz/15 Amps
- Connected Load (kW Rating) @ 115 Volts = 0.15 kW  
(For use on adequately wired 115V, dedicated circuit having 2-wire service with a separate ground wire. Appliance must be grounded for safe operation.)
- Amps @ 115V = 1.5A
- Electrical cable supplied.
- Always consult local and national electric codes.
- Unit is designed for either freestanding or built-in, under-counter installation with right or left door swing.
- Built-in, under-counter installation does not require additional airspace for top, sides or rear of unit.
- Proper built-in, under-counter installation requires that both electrical outlet and plug be completely recessed to ensure unit will fit flush against rear wall.
- To allow for ease of installation and removal, it is recommended that cabinet rough opening dimensions be increased by at least  $\frac{1}{4}$ " over product's dimensions.
- For proper ventilation, unit can NOT be installed behind closed doors; front grille MUST remain unobstructed.
- Must be positioned on flat, level surface, capable of supporting entire weight when fully loaded.
- Leveling legs supplied to adjust height and level unit.
- Do not position unit near any heat source to ensure optimum performance.
- Unit requires zero clearance when installing flush with cabinet or wall.
- When installing against cabinet or wall that extends beyond front edge of unit, 2-1/2" minimum handle clearance required to allow for 90° door swing, providing sliding shelves with necessary clearance.

**Note: For planning purposes only. Refer to Product Installation Guide on the web at [electroluxappliances.com](http://electroluxappliances.com) for detailed instructions.**

## Electrolux Major Appliances, N.A.

USA • 10200 David Taylor Drive • Charlotte, NC 28262 • 1-877-4electrolux (1-877-435-3287) • [electroluxappliances.com](http://electroluxappliances.com)  
CANADA • 5855 Terry Fox Way • Mississauga, ON L5V 3E4 • 1-800-265-8352 • [electroluxappliances.ca](http://electroluxappliances.ca)

EI24BC10Q 08/16

© 2016 Electrolux Home Products, Inc.



High standards of quality at Electrolux Home Products, Inc. mean we are constantly working to improve our products. We reserve the right to change specifications or discontinue models without notice.