

Monitor Section

Picture size	6.75 inches(diagonal) wide
W x H	151.8 mm x 79.68 mm, 5-31/32 x 3-1/8 inch
Display system	TN LCD panel
Drive system	TFT active matrix system
Number of pixels	1,152,000 800H x 480V x RGB
Effective pixels	99.99%
Pixel arrangement	RGB striped arrangement
Back lighting	LED

DVD Section

D/A Converter		24 / 32Bit
Audio Decoder		Linear PCM Dolby Audio MP3 / WMA / AAC / WAV / FLAC / Vorbis
Video Decoder		MPEG1/2,MPEG4 / WMV / H.264 / MKV
Wow & Flutter		Below Measurable Limit
Frequency response	96k Sampling	20 - 44,000 Hz
	48k Sampling	20 - 22,000 Hz
	44.1k Sampling	20 - 20,000 Hz
Total harmonic distortion 1kHz		0.010%
Signal to Noise ratio		90.5dB (DVD-Video 96k)
Dynamic range		89dB (DVD-Video 96k)
DISC Format		DVD-Video / VIDEO-CD / CD-DA
Quantifying bit number		16 / 20 / 24bit

USB I/F Section

USB Standard	USB2.0 High Speed
File System	FAT 16/32, exFAT, NTFS
Maximum Power Supply Current	DC5V=1.5A
D/A Converter	24/32Bit
Audio Decoder	MP3 / WMA / AAC / WAV / FLAC / Vorbis
Video Decoder	MPEG1/2,MPEG4 / WMV / H.264 / MKV

Bluetooth Section

Technology	Bluetooth Ver4.1
Frequency	2.402 – 2.480 GHz

Monitor Section

Picture size	6.75 inches(diagonal) wide
W x H	151.8 mm x 79.68 mm, 5-31/32 x 3-1/8 inch
Display system	TN LCD panel
Drive system	TFT active matrix system
Number of pixels	1,152,000 800H x 480V x RGB
Effective pixels	99.99%
Pixel arrangement	RGB striped arrangement
Back lighting	LED

DVD Section

D/A Converter		24 / 32Bit
Audio Decoder		Linear PCM Dolby Audio MP3 / WMA / AAC / WAV / FLAC / Vorbis
Video Decoder		MPEG1/2,MPEG4 / WMV / H.264 / MKV
Wow & Flutter		Below Measurable Limit
Frequency response	96k Sampling	20 - 44,000 Hz
	48k Sampling	20 - 22,000 Hz
	44.1k Sampling	20 - 20,000 Hz
Total harmonic distortion 1kHz		0.010%
Signal to Noise ratio		90.5dB (DVD-Video 96k)
Dynamic range		89dB (DVD-Video 96k)
DISC Format		DVD-Video / VIDEO-CD / CD-DA
Quantifying bit number		16 / 20 / 24bit

USB I/F Section

USB Standard	USB2.0 High Speed
File System	FAT 16/32, exFAT, NTFS
Maximum Power Supply Current	DC5V=1.5A
D/A Converter	24/32Bit
Audio Decoder	MP3 / WMA / AAC / WAV / FLAC / Vorbis
Video Decoder	MPEG1/2,MPEG4 / WMV / H.264 / MKV

Bluetooth Section

Technology	Bluetooth Ver4.1
Frequency	2.402 – 2.480 GHz

Monitor Section

Picture size	6.75 inches(diagonal) wide
W x H	151.8 mm x 79.68 mm, 5-31/32 x 3-1/8 inch
Display system	TN LCD panel
Drive system	TFT active matrix system
Number of pixels	1,152,000 800H x 480V x RGB
Effective pixels	99.99%
Pixel arrangement	RGB striped arrangement
Back lighting	LED

DVD Section

D/A Converter		24 / 32Bit
Audio Decoder		Linear PCM Dolby Audio MP3 / WMA / AAC / WAV / FLAC / Vorbis
Video Decoder		MPEG1/2,MPEG4 / WMV / H.264 / MKV
Wow & Flutter		Below Measurable Limit
Frequency response	96k Sampling	20 - 44,000 Hz
	48k Sampling	20 - 22,000 Hz
	44.1k Sampling	20 - 20,000 Hz
Total harmonic distortion 1kHz		0.010%
Signal to Noise ratio		90.5dB (DVD-Video 96k)
Dynamic range		89dB (DVD-Video 96k)
DISC Format		DVD-Video / VIDEO-CD / CD-DA
Quantifying bit number		16 / 20 / 24bit

USB I/F Section

USB Standard	USB2.0 High Speed
File System	FAT 16/32, exFAT, NTFS
Maximum Power Supply Current	DC5V=1.5A
D/A Converter	24/32Bit
Audio Decoder	MP3 / WMA / AAC / WAV / FLAC / Vorbis
Video Decoder	MPEG1/2,MPEG4 / WMV / H.264 / MKV

Bluetooth Section

Technology	Bluetooth Ver4.1
Frequency	2.402 – 2.480 GHz

Monitor Section

Picture size	6.75 inches(diagonal) wide
W x H	151.8 mm x 79.68 mm, 5-31/32 x 3-1/8 inch
Display system	TN LCD panel
Drive system	TFT active matrix system
Number of pixels	1,152,000 800H x 480V x RGB
Effective pixels	99.99%
Pixel arrangement	RGB striped arrangement
Back lighting	LED

DVD Section

D/A Converter		24 / 32Bit
Audio Decoder		Linear PCM Dolby Audio MP3 / WMA / AAC / WAV / FLAC / Vorbis
Video Decoder		MPEG1/2,MPEG4 / WMV / H.264 / MKV
Wow & Flutter		Below Measurable Limit
Frequency response	96k Sampling	20 - 44,000 Hz
	48k Sampling	20 - 22,000 Hz
	44.1k Sampling	20 - 20,000 Hz
Total harmonic distortion 1kHz		0.010%
Signal to Noise ratio		90.5dB (DVD-Video 96k)
Dynamic range		89dB (DVD-Video 96k)
DISC Format		DVD-Video / VIDEO-CD / CD-DA
Quantifying bit number		16 / 20 / 24bit

USB I/F Section

USB Standard	USB2.0 High Speed
File System	FAT 16/32, exFAT, NTFS
Maximum Power Supply Current	DC5V=1.5A
D/A Converter	24/32Bit
Audio Decoder	MP3 / WMA / AAC / WAV / FLAC / Vorbis
Video Decoder	MPEG1/2,MPEG4 / WMV / H.264 / MKV

Bluetooth Section

Technology	Bluetooth Ver4.1
Frequency	2.402 – 2.480 GHz

Monitor Section

Picture size	6.75 inches(diagonal) wide
W x H	151.8 mm x 79.68 mm, 5-31/32 x 3-1/8 inch
Display system	TN LCD panel
Drive system	TFT active matrix system
Number of pixels	1,152,000 800H x 480V x RGB
Effective pixels	99.99%
Pixel arrangement	RGB striped arrangement
Back lighting	LED

DVD Section

D/A Converter		24 / 32Bit
Audio Decoder		Linear PCM Dolby Audio MP3 / WMA / AAC / WAV / FLAC / Vorbis
Video Decoder		MPEG1/2,MPEG4 / WMV / H.264 / MKV
Wow & Flutter		Below Measurable Limit
Frequency response	96k Sampling	20 - 44,000 Hz
	48k Sampling	20 - 22,000 Hz
	44.1k Sampling	20 - 20,000 Hz
Total harmonic distortion 1kHz		0.010%
Signal to Noise ratio		90.5dB (DVD-Video 96k)
Dynamic range		89dB (DVD-Video 96k)
DISC Format		DVD-Video / VIDEO-CD / CD-DA
Quantifying bit number		16 / 20 / 24bit

USB I/F Section

USB Standard	USB2.0 High Speed
File System	FAT 16/32, exFAT, NTFS
Maximum Power Supply Current	DC5V=1.5A
D/A Converter	24/32Bit
Audio Decoder	MP3 / WMA / AAC / WAV / FLAC / Vorbis
Video Decoder	MPEG1/2,MPEG4 / WMV / H.264 / MKV

Bluetooth Section

Technology	Bluetooth Ver4.1
Frequency	2.402 – 2.480 GHz

Monitor Section

Picture size	6.75 inches(diagonal) wide
W x H	151.8 mm x 79.68 mm, 5-31/32 x 3-1/8 inch
Display system	TN LCD panel
Drive system	TFT active matrix system
Number of pixels	1,152,000 800H x 480V x RGB
Effective pixels	99.99%
Pixel arrangement	RGB striped arrangement
Back lighting	LED

DVD Section

D/A Converter		24 / 32Bit
Audio Decoder		Linear PCM Dolby Audio MP3 / WMA / AAC / WAV / FLAC / Vorbis
Video Decoder		MPEG1/2,MPEG4 / WMV / H.264 / MKV
Wow & Flutter		Below Measurable Limit
Frequency response	96k Sampling	20 - 44,000 Hz
	48k Sampling	20 - 22,000 Hz
	44.1k Sampling	20 - 20,000 Hz
Total harmonic distortion 1kHz		0.010%
Signal to Noise ratio		90.5dB (DVD-Video 96k)
Dynamic range		89dB (DVD-Video 96k)
DISC Format		DVD-Video / VIDEO-CD / CD-DA
Quantifying bit number		16 / 20 / 24bit

USB I/F Section

USB Standard	USB2.0 High Speed
File System	FAT 16/32, exFAT, NTFS
Maximum Power Supply Current	DC5V=1.5A
D/A Converter	24/32Bit
Audio Decoder	MP3 / WMA / AAC / WAV / FLAC / Vorbis
Video Decoder	MPEG1/2,MPEG4 / WMV / H.264 / MKV

Bluetooth Section

Technology	Bluetooth Ver4.1
Frequency	2.402 – 2.480 GHz
Bluetooth Class	Class 2