

SBC695OSNK



34.25" x 23.88" x 25" (H x W x D)

Outdoor/indoor commercial beer dispenser for built-in or freestanding use, digital thermostat, and 304 grade stainless steel exterior; no tap kit included

Highlights:

- Commercially listed to NSF-7 standards
- Flexible design allows built-in or freestanding use in 24" spaces
- Full-sized capacity can store a full half barrel, two slim quarter barrels, or up to three Cornelius style or sixtels

Product Features:

| | |
|---------------------------|---|
| Commercially approved | ETL-S listed to NSF-7 commercial standards and meets UL-471 for use in foodservice settings |
| Weatherproof design | Solid construction allows placement in the outdoors |
| Built-in capable | Front-breathing design allows fully recessed installation under counters |
| Full-sized beer dispenser | Large interior can accept a full half barrel keg, two slim quarter kegs, or up to three sixth barrel or Cornelius style kegs |
| No tap kit included | Install your own tapping system for a customized beer cooler |
| Stainless steel exterior | Door and cabinet are wrapped in 304 grade stainless steel for lasting durability in the outdoors |
| Professional handle | Blade style handle in brushed stainless steel matches many popular styles of cabinetry and grill details |
| Digital thermostat | Electronic controls ensure easy temperature management for optimum beer storage, with a readout viewable in Celsius or Fahrenheit |
| Automatic defrost | No-frost operation for minimum user maintenance |

SBC695OSNK Specifications:

| Overview | |
|----------------------------|-----------------------|
| Height of Cabinet | 34.25" (87 cm) |
| Width | 23.88" (61 cm) |
| Depth | 25.0" (64 cm) |
| Depth with Handle | 26.88" (68 cm) |
| Depth with door at 90° | 47.75" (121 cm) |
| Capacity | 6.04 cu.ft. (171 L) |
| Defrost Type | Automatic |
| Door | Stainless Steel |
| Cabinet | Stainless Steel |
| US Electrical Safety | ETL |
| Canadian Electrical Safety | ETL-C |
| Sanitation | ETL-S |
| Amps | 1.3 |
| Voltage/Frequency | 115 V AC/60 Hz |
| Weight | 108.0 lbs. (49 kg) |
| Shipping Weight | 113.0 lbs. (51 kg) |
| Estimated Time to Ship | Next day shipping |
| Parts & Labor Warranty | 1 Year |
| Compressor Warranty | 5 Years |
| Kegeerator | |
| Door Swing | RHD |
| Reversible | Yes |
| Height with Tap | 50.38" (128 cm) |
| Thermostat Type | Digital |
| Interior Light | Yes |
| Fan Type | Interior and Exterior |
| Refrigerant | R600a |
| Refrigerant Amount | 1.76 oz. |
| High Side PSI | 220.0 |
| Low Side PSI | 43.0 |
| Inter Height | 27.0" (69 cm) |
| Interior Width | 20.38" (52 cm) |
| Interior Depth | 21.25" (54 cm) |
| Compressor Step Height | 5.5" (14 cm) |
| Compressor Step Width | 9.63" (24 cm) |
| Compressor Step Depth | 2.5" (6 cm) |
| Wheel Qty | 4 |

| | |
|-------------------|-----------------|
| Surface | Stainless Steel |
| Temperature Range | 32° to 50°F |

