

## Fully Integrated 24" Wine Storage System

KWT 1613 Vi / KWT 1603 Vi



# Fully Integrated 24" Wine Storage System

## KWT 1613 Vi / KWT 1603 Vi



### Features:

- MasterCool controls
- ClearView lighting system
- 14 Rack Levels
- Stores up to 102 bottles
- FullView extendable shelves
- RemoteVision capable
- Acoustic door and temperature alarm
- Optical door and temperature alarm

### SPECIFICATIONS

KWT 1603 Vi — Item 36160301USA - Right Hinged

KWT 1613 Vi — Item 36161301USA - Left Hinged

Overall Unit Width 23<sup>3</sup>/<sub>4</sub>" (603 mm)

Overall Unit Height 83<sup>1</sup>/<sub>2</sub>" - 85<sup>3</sup>/<sub>16</sub>" (2121 mm - 2165 mm)

Overall Unit Depth 24" (610 mm)

#### Niche

Minimum Cabinet Opening Width 24" (610 mm)

Minimum Cabinet Opening Height 83<sup>5</sup>/<sub>8</sub>" (2124 mm)

Minimum Cabinet Opening Depth 25" (635 mm)\*

#### Electrical

Electrical Requirements - Volts/Amps 110V / 120V, 60Hz, 15 Amps  
In the case of side-by-side installations, a separate outlet must be used for each appliance.

Power Cord - Plug and length Yes - NEMA 5-15 plug, 5 ft (1.52 m)

#### Custom Panel

**Please refer to the manual for further details.**

Maximum Panel Weight 137 lbs (62 kg)

Maximum Panel Thickness 1<sup>1</sup>/<sub>2</sub>" (38 mm)

Minimum Panel Thickness <sup>3</sup>/<sub>4</sub>" (19 mm)

#### Shipping

Shipping Weight 374.4 lbs (170 kg)

Shipping Dimensions 27<sup>1</sup>/<sub>2</sub>" W x 89<sup>13</sup>/<sub>16</sub>" H x 29<sup>1</sup>/<sub>4</sub>" D

#### Support

Call Miele 800.843.7231

Miele Website [www.mieleusa.com](http://www.mieleusa.com)



20/20 Link [2020technologies.com](http://2020technologies.com)

# Fully Integrated 24" Wine Storage System

## KWT 1613 Vi / KWT 1603 Vi



FOR FLUSH INSTALLATION



\* Niche depth assumes a 3/4" (19 mm) panel, please adjust according to custom panel thickness

| Location Codes   |
|--|
| E - 5 foot - 120 Volt - 15 Amp 3-wire molded plug power supply connects lower left rear  |
| O - Standard NEMA 5-15 Outlet - locate less than 9" above finished floor   |
| Notes  |
| <ul style="list-style-type: none"><li>• All Installations must be done in accordance with local codes</li><li>• Sides of adjoining cabinets should be filled (flush to frame) to insure proper fit and finish</li><li>• For Proud Installation - please adjust accordingly</li></ul> |


# Fully Integrated 24" Wine Storage System

## KWT 1613 Vi / KWT 1603 Vi




### POWER SUPPLY CONNECTION BACK VIEW

*Electrical - 5 foot (1.52 m) - 120 Volt - 15 Amp -  
NEMA 5-15 molded plug*



### GLASS DIMENSIONS FRONT VIEW



#### Notes

- Centerpoint is 45 1/2" (1155 mm) with typical 84" (2134 mm) installation

# Fully Integrated 24" Wine Storage System


## KWT 1613 Vi / KWT 1603 Vi



### CUSTOM PANEL INSTALLATIONS

**These units do not come equipped with a front panel.** They are designed to accept a custom door panel supplied by the cabinet maker. Miele has a unique panel integration system which allows the panels to align with the surrounding cabinets.

Panel size is determined in the following manner:



**Width:** 23 3/4" (603 mm) in all cases

**Thickness:** Minimum 3/4" (19 mm) outside frame

**Height:** Determined using the following calculation:

$$\text{Panel Height} = \text{HOC} - \text{TKH}$$

**HOC** = Total height of cabinet or side panel


**TKH** = Toe-kick height

**Note:** Finish back side of panels to insure appearance  
Panel may extend above unit. This is **not** considered in height calculation

**Maximum panel weight** 137 Pounds

## Panel Notes

If the adjoining cabinets are taller than the height of machine (HOM) - the front panel may be extended accordingly. Simply maintain the toekick height and extend the panel the needed distance.



# Fully Integrated 24" Wine Storage System


## KWT 1613 Vi / KWT 1603 Vi




### HINGING DETAILS

#### 90° Door

Thickness options




Door Swing




**NOTE:** Additional space needed depending on thickness of front panels and handle used

#### 115° Door

Thickness options



Door Swing




**NOTE:** Additional space needed depending on thickness of front panels and handle used

# Fully Integrated 24" Wine Storage System

## KWT 1613 Vi / KWT 1603 Vi



### HINGING DETAILS 115° OPENING







# Fully Integrated 24" Wine Storage System KWT 1613 Vi / KWT 1603 Vi



## HINGING DETAILS 90° OPENING



*When installing hinge side next to an appliance or object that is within range of the door panel, limit the door opening angle to 90°. This is done by installing the banking pin as illustrated. Insert the banking pin through the holes and drive in with a hammer.*