Product data sheet

CONSTRUCTION TYPE	
Built-in appliance	•
Integrated appliance	•
Door hinging	Left
Convertible hinging	•
Can be installed side by side	•
DESIGN	
Lighting	BrilliantLight
USER CONVENIENCE	
FullAccess	•
EasyClean	•
MaxLoad hinge	•
IceMaker with fresh-water connection	•
NoFrost	•
NoFrost	•
SoftClose	•
Push2open	•
Networking with Miele@home	•
CONTROLS	
Eco mode	•

10/12/23, 11:20 AM F 2412 Vi | Miele

User interface	MasterSensor
SuperFrost	•
Number of temperature zones	1
Sabbath mode	•
FRIDGE / FRIDGE SECTION	
Door baskets – small	1
Door baskets – large	3
FREEZER / FREEZER SECTION	
Number of shelves	2
Number of freezer baskets	2
EFFICIENCY AND SUSTAINABILITY Energy Star	•
SAFETY	
Safety lock	•
Acoustic door alarm	•
Acoustic temperature alarm, freezer section	•
Optical door alarm	•
Optical temperature alarm	•
TECHNICAL DATA	

Replacing lamps

Customer Service

10/12/23, 11:20 AM F 2412 Vi | Miele

Number of phases	1
Niche width in inches (mm), min.	18 (457)
Niche width in inches (mm), max.	18 (457)
Niche height in inches (mm), min.	84 1/8 (2134)
Niche height in inches (mm), max.	84 1/8 (2134)
Niche depth in mm	24 7/8 (629)
Appliance width in mm	17 7/8 (451)
Appliance height in mm	83 3/4 (2125)
Appliance depth in mm	24 (608)
Weight in Ibs (kg)	264 (119.3)
Door hinge technology	Fixed door
Max. weight of door, fridge section, in kg	131 (59)
Total usable capacity in I	8.48 (240) ft³ (I)
Current consumption in milliamps (mA)	4000
Voltage in V	110-120
Fuse rating in A	10
Frequency in Hz	60
Length of power cable in m	11 (3.5)

APPLIANCE CATEGORY

Freezer

AVAILABLE DISPLAY LANGUAGES

Available display languages via Language Options

bahasa malaysia