## LUMIX G X Vario Lens, 35-100mm, F2.8 ASPH., Professional Micro Four Thirds, POWER Optical I.S. - H-HS35100 H-HS35100

<ul> <li>Lens Construction 18 elements in 13 groups (2 ED lenses,1 UED lens)</li> <li>Nano Surface Coating Yes</li> </ul>
o Nano Surface Coating Yes
_
• Mount Micro Four Thirds mount
<ul> <li>Optical Image Stabilizer Yes (POWER O.I.S.)</li> </ul>
• Focal Length f=35-100mm (35mm camera equivalent 70-200mm)
• Aperture Type 7 diaphragm blades / Circular aperture diaphragm
o Maximum Aperture F2.8
o Minimum Aperture F22
• Closest Focusing Distance 0.85m / 2.8ft
• Maximum magnification Approx. 0.1x / 0.2x (35mm camera equivalent)
Diagonal Angle of View 34°(Wide) to 12°(TELE)
• Filter Size φ58mm / 2.3in
<ul> <li>Max. Diameter Approx. φ67.4mm / 2.7in</li> </ul>
• Overall Length Approx. 99.9mm / 3.9in (from the tip of the lens to the base side of the lens mount)
• Weight Approx. 360g / 12.7oz (excluding lens cap ,lens rear cap,lens hood)
ns
<ul> <li>Standard Accessories Lens front cap, Lens rear cap, Lens hood, Lens storage bag</li> </ul>
Color black