

UP30W



Colour range

Body



Blue
grey – BG



White – WH



Stainless
steel – SS



Graphite
matt – MG



Glossy
black – BK



Satin

RAL

Optional RAL – RA

+

Finishes

Knobs, handles

Optional solid door version

optional +

Order code: change letter "W" with "Q"

Available ovens


Electric oven

Primary oven:
UOV 76 M


Maximum input:
3.7 kW

Configurations

5 burners



Induction



Electric oven

UP30WMP

Brushed

UPI304WMP

Brushed

Fuel requirements

Natural gas / Liquid propane
Voltage: 240 Volts
Amps: 15.4

All electric
Voltage: 240 Volts
Amps: 47.5

**Insufficient amperage may lower heating performance when multiple functions are being used at the same time*

Consumption

Bridge induction zone
Ø 7" 1/4 + Ø 7" 1/4
1.85 / 2.5 kW + 1.85 kW

Small burner
7000 btu/h / 1400 btu/h

Induction zone
Ø 5" 3/4
1.4 / 1.8 kW

Induction zone
Ø 7" 1/4
1.85 / 2.5 kW

Induction zone
Ø 8" 11/16
2.3 / 3.2 kW

Double ring Dual burner
25000 btu/h / 900 btu/h

Big burner
10500 btu/h / 2000 btu/h

Complements & accessories

Hood

UAGQ30

Ladle holder panel

AM4-76

Technical drawing & dimensions

