#### IMPORTANT

For built-in applications only! Ensure the anti-tip brackets are installed per the installation manual that came with the cabinet. Never install if used with caster kits or extended leg kits.

**Tools Required** 



5/32" DRILL BIT

JMP

	Parts Required								
Part Number	Description	HP15		HP24, HC24, & HA24		HH24		HP48	
		Left Hinged Door	Right Hinged Door	Left Hinged Door	Right Hinged Door	Left Hinged Door	Right Hinged Door	Left & Right Hinged Dool	
69608-1	15" Grill, Left Hinged Door	1	-	-	-	-	-	-	
69609-1	15" Grill, Right Hinged Door	-	1	-	-	-	-	-	
68837	15" Grill Mounting Bracket	1	1	-	-	-	-	-	
69603-1	24" Grill, Left Hinged Door	-	-	1	-	1	-	1	
69604-1	24" Grill, Right Hinged Door	-	-	-	1	-	1	1	
68836	24" Grill Mounting Bracket	-	-	1	1	1	1	2	
68094-15	15" Mounting Plate	1	1	-	-	-	-	-	
68094-24	24" Mounting Plate	-	-	1	1	-	-	-	
68094-24x18	24" x 18" Mounting Plate	-	-	-	-	1	1	-	
68094-48	48" Mounting Plate	-	-	-	-	-	-	1	
63965	Latch Strike	2	2	2	2	2	2	4	
63966	Latch	2	2	2	2	2	2	4	
C31323	Bumper, Adjesive Poly	4	4	4	4	4	4	8	
M00885-189	1/4-20 x 1/2" Machine Screw	4	4	4	4	4	4	6	
M50050-466	#10 x 1/2" Sheet Metal Screw	4	4	4	4	4	4	11	



OR MECHANICAL, INCLUDING PHOTOCOPYING, RECORDING, OR USED IN ANYINFORMATION STORAGE, TRANSMISSION, OR RETRIEVAL SYSTEM, WITHOUT WRITTEN PERMISSION FROM THE PERLICK CORPORATION COPYRIGHT 2001 PERLICK CORPORATION ALL RIGHTS RESERVED

**CAUTION:** These cabinets are extremely heavy. Ensure that you have enough people on hand to help in repositioning the units so that it can be done safely and without damage.

Step 1: Drill out top row of rivets along back of the bottom cabinet using a 5/32" drill bit.



Step 3: Attach mounting plate (where the leg levelers were removed in step 2) by using 1/4-20 machine screws. Flange should be pointing away from the bottom of the unit.



Step 4: Place upper unit on top of lower unit and attach using #10 sheet metal screws (where the rivets were drilled out in step 1).



Step 5: Remove (2) #10 sheet metal screws from the front of the top cabinet (These screws will be used to attach the mounting bracket) Attach mounting bracket(s) to the front of the cabinet using #10 sheet metal screws. Install latches into the grill bracket(s).



Step 6: Attach (4) bumpers and (2) latch strikes to each new grill. Orient the tabs on the latch strike vertically. Attach grill assembly to upper unit. Move stacked assembly into final position by pushing lower unit.

