### SUMMIT

# SEH1530SSADA



#### 37.25" x 29.5" x 19.69" (H x W x D)

30" wide ADA-compliant European-style convertible wallmounted range hood in stainless steel with remote wall switch

#### **Highlights:**

ADA-compliant design allows you to control the hood from a wall light switch for easier accessibility

30" wide wall-mounted range hood

Versatile design for ducted or recirculating operation with a set of carbon filters included

#### **Product Features:**

30" wide wall-mounted range hood	European style range hood designed to bring effective ventilation over 30" wide cooking surfaces
ADA-compliant design	Control panel comes on a remote terminal block to be installed according to ADA compliant guidelines for improved accessibility (some assembly required)
Convertible design with no additional purchase necessary	Can be used for ducted venting to the outside or recirculating ventilation where no external venting is possible
Charcoal filter set included	Two round carbon filters attach to the blower to absorb grease and odors when using the hood in recirculating mode
Powerful ventilation	400 CFM blower to effectively remove smoke and cooking odors from your kitchen
Cord included	Pre-installed power cord with 3-prong plug for 115V outlets
LED lighting (bulbs included)	Includes two pre-installed LED bulbs to illuminate your cooking surface
Adjustable height	Includes a telescoping chimney extender that allows you to adjust the overall height between 25 1/2" to 37 1/4"
Stainless steel finish	Durable construction in an attractive style with a horizontal grain

SUMMIT APPLIANCE DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified 770 Garrison Avenue Bronx, NY 10474 USA TEL 718-893-3900 FAX 844-478-8799

info@summitappliance.com



## SUMMIT

### SEH1530SSADA Specifications:

Overview		
Height of Cabinet	37.25" (95 cm)	
Width	29.5" (75 cm)	
Depth	19.69" (50 cm)	
Door	Stainless Steel	
US Electrical Safety	ETL	
Amps	2.6	
Voltage/Frequency	115 V AC/60 Hz	
Weight	40.0 lbs. (18 kg)	
Shipping Weight	47.0 lbs. (21 kg)	
Parts & Labor Warranty	1 Year	
UPC	761101086774	
Range Hood		
Range Hood		
Range Hood Installation	Wall-Mounted	
	Wall-Mounted Convertible	
Installation		
Installation Venting	Convertible	
Installation Venting Controls	Convertible Slide	
Installation Venting Controls Light	Convertible Slide Yes	
Installation Venting Controls Light Number of Lights	Convertible Slide Yes 2	
Installation Venting Controls Light Number of Lights Light Type	Convertible Slide Yes 2 LED	
Installation Venting Controls Light Number of Lights Light Type Number of Fan Speeds	Convertible Slide Yes 2 LED 3	
Installation Venting Controls Light Number of Lights Light Type Number of Fan Speeds Maximum Air Movement	Convertible Slide Yes 2 LED 3 400.0 CFM	
Installation Venting Controls Light Number of Lights Light Type Number of Fan Speeds Maximum Air Movement Minimum Height	Convertible Slide Yes 2 LED 3 400.0 CFM 25.5" (65 cm)	



