

T18IF100SP

18-INCH BUILT-IN FREEZER COLUMN WITH INTERNAL ICE MAKER

FREEDOM® COLLECTION, PANEL-READY



FEATURES & BENEFITS

- ★ - Our next-generation Free Flow™ Cold Air continuously circulates cold air to prevent temperature swings for precise cooling top to bottom, drawer to door
- All metal door bins, sleek glass shelving, and durable glass and metal SoftClose™ drawers—perfectly crafted for stylish functionality that stands the test of time
- ★ - Overhead Skylight™ & side wall LEDs cast brilliant, multi-directional light, eliminating shadows and making all items easy to find
- Effortlessly control temperature, lighting, ice, & other settings on a durable LED touchscreen, ensuring easy access for your convenience or remotely through our Home Connect® App
- ★ - Our all-new exclusive mini Diamond ice shape, is designed for rapid & uniform cooling, with a quick ice function for unexpected moments
- Flexible organization with adjustable shelves and door bins, for effortless, customized organization
- ★ - SuperFreeze® drops to -15°F, rapidly restoring softening ice creams, meats, and other goods to their optimal frozen state

STYLE

Door Style	Custom Panel
Standard Door Swing (Optional Reversal Kit Available for Purchase)	Left Hinge
Handle Style	Custom Handle
Interior Finish	Stainless Steel

INNOVATION

Wi-Fi-Enabled For Control w/Home Connect® App	Yes
Remote Monitoring and Control	Yes
Remote System Upgrade	Yes
Overhead Skylight™ and Side Wall LEDs	Yes
Auto-Dim Illumination	Yes
Mini Diamond Ice	Yes

PERFORMANCE

Quick Ice	Yes
Automatic Defrosting	Yes

Modes

Eco, Sabbath, Demo, Quick Ice, SuperFreeze®

UltraClarityPro® Water Filter (6 Months)	Yes
--	-----

CAPACITY AND STORAGE

Total Capacity (cu. ft.)	9.9
Full-Extension Freezer Storage Drawer	2
Full-Extension Icemaker Drawer	1
Storage Shelves	3 Adjustable, 1 Fixed
Metal Door Bins	3 Adjustable, 1 Fixed

GENERAL FEATURES

Touch Screen LED Panel	Yes
Water Filter Replacement Indicator	Yes
Single Ice Maker with Mini Diamond Ice	Yes
Mini Diamond Ice 24 Hr. Production (lbs.)	2.4
Quick Ice 24 Hr. Ice Production (lbs.)	3.2
Ice Storage Capacity (lbs.)	2.6
Ice On / Off	Yes
LED Interior Lighting	Yes
Open Door Assist	Yes
Open Door Alarm	Yes
Childproof Lock	Yes
Cooling System	Free Flow™ Cold Air
Maximum Sound Level	39 dBA
SoftClose™ Door	Yes
SoftClose™ Drawers	Yes
Star-K Certified Sabbath Mode	Yes
ENERGY STAR® Certified	Yes
Annual Energy Consumption	385 kWh / yr*

*Estimated annual energy consumption. Exact usage may vary.

★ THERMADOR® EXCLUSIVE

T18IF100SP
18-INCH BUILT-IN FREEZER COLUMN WITH
INTERNAL ICE MAKER
FREEDOM® COLLECTION, PANEL-READY



OPERATING TEMPERATURE

Freezer: -7°F (-22°C) to 6°F (-14°C)

SuperFreeze®: -15°F (-26°C) for Approximately 8 Hours

INSTALLATION FEATURES

Pocket Handle Door Design Yes

Four Point Front Adjustable with 4 Wheels Yes

Attachment Method to Cabinetry

4 Fixation Brackets, Fixed at 4 Corners of Appliance, No Visible Screws

Front Serviceable Yes

Anti-tip Bracket Included Yes

Side Trim Kit Included Yes

Door Reversible Yes

TECHNICAL SPECS

Required Power Supply 110-120 V, 60 Hz,
Min. 10 Amp

Plug Type 3-Prong

Power Cord Length (Inches) 118"

DIMENSIONS AND WEIGHT

Appliance Dimensions (HxWxD) (inches) 83 7/8" Min. –
85 1/2" Max. x
17 3/4" x 24"

Required Cutout Size (HxWxD) (Inches) 84" x 18" x 25"

Net Weight (Approx.) (lbs.) 307

Gross Weight (Approx.) (lbs.) 341

OPTIONAL ACCESSORIES

Stainless Steel Door Panel, Handleless Design TFL18IF105

Stainless Steel Door Panel, Handle Ready Design TFL18IF100

Door Direction Change Kit DOORDIR18

Professional Handle PR36HNDL20

Masterpiece® Handle MS36HNDL20

Frame Kit FRAMEKIT30

Combination Kit COMBIKIT10

Retrofit Combination Kit COMBIKIT20

Replacement UltraClarityPro® Water Filter REPLFLTR55

Replacement Ethylene Starter Kit (Part No.) 17006999

Replacement Ethylene Filter Packets (Part No.) 17007000

Water Filter Bypass (Part No.) 11049963

WARRANTY

Limited Warranty, Parts & Labor 2 Years

Limited Warranty, Sealed System and Compressor, Parts & Labor 6 Years

Limited Warranty, Sealed System and Compressor, Parts Only 12 Years

Limited Warranty for Stainless Steel Rust-Through Lifetime

SUPPLEMENTAL MATERIAL

CAD File [Click Here to Download](#)

Installation Manual [Click Here to Download](#)

Use & Care Guide [Click Here to Download](#)

Warranty [Click Here to Download](#)

Energy Guide [Click Here to Download](#)

Home Connect® Quick Start Guide [Click Here to Download](#)



T18IF100SP



18-INCH BUILT-IN FREEZER COLUMN WITH INTERNAL ICE MAKER

FREEDOM® COLLECTION, PANEL-READY



FLUSH INSTALL CUTOUT DIMENSIONS

Measurements in inches (mm)



- A:** Socket
B: Area for water and electric line routing
C: Furniture return
 C1: Frameless cabinet
 C2: Framed cabinet
D: Filler

PLANNING NOTES

Depth: The freezer is fully flush integrated when installed in a 25" (635mm) deep cabinets with a typical panel thickness of 3/4" (19mm). Recess depth depends on kitchen design and panel thickness.



Electrical Supply: The electrical supply outlet (A) is recommended to be located in an adjacent cabinet for safety and serviceability. If it is not possible due to the construction to connect the appliance to a power outlet next to it (A), connect the appliance to a power outlet behind the appliance (B). This alternative position of the power outlet is permissible only if you can switch off the outlet with a circuit breaker in the fuse box.

Water Supply: A cold water connection is required for appliances that feature an ice maker or an ice and water dispenser. Water pressure must be between 40 and 120 p.s.i. A separate shut-off valve must be installed for the appliance water connection. The shut-off valve for the water connection may not be behind the appliance. It is recommended to place the shut-off valve outside the cutout next to the appliance or in another easily accessible location. When installing the water connection, observe the permitted installation areas for the water supply line.

Furniture Return: The interior sides of the furniture return (C) will be partially visible when the refrigerator door is opened. Top and side returns should be finished to match the exterior furniture at a minimum depth of 4" (102 mm). Ensure that the side walls of the cutout (C) are completely flush to a depth of at least 4" (102 mm).

FLUSH INSTALL TOP VIEW CLEARANCES

Measurements in inches (mm)



A: Panel

PLANNING NOTES

Door Panels & Handles: Clearance dimensions are based on a door panel (A) thickness of 3/4" (19mm). Additional clearances must be added for handles and door panels thicker than 3/4" (19mm).

Clearance Requirements: The required clearances for the maximum door opening angle of 115° should be followed. The minimum required clearance to fully access all compartments is 90° door opening (B).


PRELIMINARY
PRELIMINARY
PRELIMINARY
PRELIMINARY
PRELIMINARY

T18IF100SP
18-INCH BUILT-IN FREEZER COLUMN WITH
INTERNAL ICE MAKER
FREEDOM® COLLECTION, PANEL-READY



PRODUCT DIMENSIONS

Measurements in inches (mm)




PLANNING NOTES

Adjustable Height: The appliance height is adjustable. Recommended height for a standard 84" niche is 83 7/8". The minimum height with leveling legs fully retracted is 83 7/8". The maximum height with leveling legs fully extended is 85 1/2".

Rear Appliance Recess: The recessed area at the base can be used for routing water and electric supply lines to the appliance.

PANEL DIMENSIONS



Measurements in inches (mm)



A: Max. weight 121 lbs (55 kg) per panel

HINGE CLEARANCE

Measurements in inches (mm)



T18IF100SP


18-INCH BUILT-IN FREEZER COLUMN WITH INTERNAL ICE MAKER

FREEDOM® COLLECTION, PANEL-READY



BASE DETAIL DIMENSIONS, SIDE VIEW



Measurements in inches (mm)



TIPPING RADIUS CLEARANCES

PLANNING NOTES

Be sure there is adequate ceiling height to stand the refrigerator upright when it is moved into place. The dolly wheel height must be added to the tipping radius when a dolly is used.



ACCESSORIES (OPTIONAL)



REPLFLTR55
(PART NO. 11032531)
UltraClarityPro® Water Filter



17006999
Ethylene Filter Starter Kit



17007000
Ethylene Filter Refill



11049963
Water Filter Bypass



PR36HNDL20
Professional Handle



MS36HNDL20
Masterpiece® Handle

IMAGE
COMING
SOON

DOODIR18
Door Direction Change Kit



TFL18IF105
Stainless Steel Door Panel,
Handless Design



TFL18IF100
Stainless Steel Door
Panel, Handle Ready
Design



FRAMEKIT30
Frame Kit



COMBIKIT10
Required for side-by-side installation of built-in columns (model# Txxxx1) and built-in bottom freezer refrigerators (model# Txxxx1)

IMAGE
COMING
SOON

COMBIKIT20
Retrofit kit required for side-by-side installation of legacy built-in columns (model# Txxxx9) with built-in columns (model# Txxxx1) or built-in bottom freezer refrigerators (model# Txxxx1)

These warranties give you specific legal rights and you may have other rights that vary from state to state. Limited warranty from date of delivery. For complete warranty details, refer to your Use & Care manual, or ask your dealer.

Specifications are for planning purposes only. Refer to installation instructions and consult your countertop supplier prior to making counter opening. Consult with a heating and ventilation engineer for your specific ventilation requirements. For the most detailed information, refer to installation instructions accompanying product or write to Thermador indicating the model number. Specifications are correct at time of printing. Thermador reserves the right to change product specifications or design without notice. Some models are certified for use in Canada. Thermador is not responsible for products that are transported from the U.S. for use in Canada.