# Product data sheet

#### **CONSTRUCTION TYPE**

Built-in appliance	•
Integrated appliance	•
Door hinging	Left convertible
Convertible hinging	•
Can be installed side by side	•

## **DESIGN**

**Lighting** BrilliantLight

## **USER CONVENIENCE**

Freshness system	MasterFresh
FullAccess	•
EasyClean	•
MaxLoad hinge	•
DynaCool	•
SoftClose	•
SelfClose	•
Push2open	•
Networking with Miele@home	•

## CONTROLS

User interface MasterSensor

10/19/23, 3:36 PM K 2612 Vi | Miele

·	·
SuperCool	•
Number of temperature zones	2
Sabbath mode	•
FRIDGE / FRIDGE SECTION	
SlidingShelf	•
Door rack for tins	1
Height-adjustable tempered glass shelves	2
Number of vegetable drawers	1
Number of crisper drawers	2
Door rack for bottles	3
EFFICIENCY AND SUSTAINABILITY	
Energy Star	•
SAFETY	
Overflow protection	•
Safety lock	•
Acoustic door alarm	•
Acoustic temperature alarm, freezer section	•
Optical door alarm	•
Optical temperature alarm	•
TECHNICAL DATA	
Replacing lamps	Customer Service
Number of phases	1

10/19/23, 3:36 PM K 2612 Vi | Miele

o, 20, 0,00	
Niche width in inches (mm), min.	24 1/8 (610)
Niche width in inches (mm), max.	24 1/8 (610)
Niche height in inches (mm), min.	84 1/8 (2134)
Niche height in inches (mm), max.	84 1/8 (2134)
Niche depth in mm	24 7/8 (629)
Appliance width in mm	23 3/4 (603)
Appliance height in mm	83 3/4 (2125)
Appliance depth in mm	24 (608)
Weight in lbs (kg)	297 (134.6)
Door hinge technology	Fixed door
Total usable capacity in I	12.96 (367) ft³ (I)
Current consumption in milliamps (mA)	4000
Voltage in V	110-120
Fuse rating in A	10
Frequency in Hz	60
Length of power cable in m	11 (3.5)

## **ACCESSORIES SUPPLIED**

Active AirClean filter

# **APPLIANCE CATEGORY**

Refrigerator

#### **AVAILABLE DISPLAY LANGUAGES**

Available display languages via Language Options

bahasa malaysia