
# GE Zoneline® Heat Pump Unit with ICR, 265 Volt



#### Model# AZ65H15EAD



- Cooling capacity 14,300 BTU
- Energy efficiency 10.4 EER
- Dehumidification 4.8 pints/hour
- Reverse heat cycle 13,500 BTU
- Heat pump efficiency 3.2 COP
- Indoor fan CFM (high/low) 449/290
- Fresh air vent CFM (fully open high fan) 44
- Quiet operation Baked-on mastic sound barrier, cross flow blower and two DC fan motors create less noise to ensure comfort
- Internal condensate removal Minimizes condensate draining from the unit during heat pump operation
- Heat & Freeze Sentinels Keeps the room from overheating or freezing
- Boost heat option Provides supplemental resistance heat in heat pump mode
- Electronic temperature limiting Prevents expensive over-cooling or over-heating of the room
- - Electronic touch controls with LED display
- - R-410A refrigerant
- - SMC base pan

• Simplified structure - Easy to maintain and service Have more questions? Please contact 1-800-626-2005

FEATURES	
Sensible Heat Ratio	60%
Chassis Type	Slide-In
Control Type	Standard Microcomputer; Tactile
	touch pad with LED Display
Discharge Grille	2-position
Electronic Micro Computer Control	Yes
Fan Cycle Switch	Yes
Fan Motor	2
Fan Speed Control	Yes
Fan Speed Selections	Hi/Low Cooling; Hi/Low Fan Only; Hi/Low Heating
Filter Type	Rigid Frame; Slide-Out
Heat - Cool	Yes
Internal Condensate Removal (ICR)	Yes
Louver Style	Reversible
Manual Vent Control	Hidden
Rotary Compressor	Yes
Temperature Limiting	Electronic 7-Step
Vent Control	3-position
Venting Features	Concealed Manual Vent Control; Outdoor Vent Control - 3 Positions; Vent Air Filter
Zoneline Features	"Sleep" Mode; "Smart Fan" Fan Cycle Control; 3-Stage Heating Design; Auto Power Recovery; Automatic Emergency Heat; Automatic Indoor Frost Control; Central Desk Control Compatibility; Freeze Sentinel; Heat Pump with Resistance Heat Backup; Heat Pump with Supplemental Resistance Heat; Heat Sentinel; LCDI Power Cord (purchased separately); Proportional - Integral ID Airflow; Quick Heat Recovery; Random Twist/Length Segment Tangential Blower; Remote Thermostat Compatibility; Reverse Cycle Defrost; Universal Heaters; Weather Protected Electrical Components
Product Type	Packaged Terminal Air Conditioners (PTAC)
Temperature Range	60 - 85 F

## GE Zoneline® Heat Pump Unit with ICR, 265 Volt



#### Model# AZ65H15EAD

- APPROXIMATE DIMENSIONS (HxDxW)
- 16 in x 20 13/16 in x 42 in

## CAPACITY

- Cooling BTUH (MIN) 14500.00 Btu
- Cooling EER (BTUH / Watt) 10.30
- CFM Indoor Fan High 400
- CFM Indoor Fan Low 290
- Dehumidification (pts./hr.) 4.80
- Heating Reverse Cycle BTUH 13,500
- Vent CFM (high fan at zero ESP) 44

## WARRANTY

- Parts Warranty Limited 1-year entire appliance; Limited 5-year sealed refrigerating system
- Labor Warranty Limited 1-year entire appliance; Limited 5-year sealed refrigerating system
- Warranty Notes See written warranty for full details