## accucold

# ARG23MLLH



#### 83.75" x 27.5" x 31" (H x W x D)

Performance series Pharma-Lab 23 cu.ft. all-refrigerator in stainless steel with glass door and left hand door swing

#### **Highlights:**

Intelligent microprocessor digital temperature controller

Improved temperature accuracy with a separate temperature probe for continuous product readout

Additional sensor reads interior air temperature for superior temperature control

#### **Product Features:**

Purpose-built design	Designed and engineered to store vaccines and other sensitive materials under stable temperature conditions	
Adjustable temperature	Interior is pre-set to 5°C, with an adjustable control range from 2 to 10°C	
Temperature alarm	Visual and audible alarms alert if the interior temperature rises or falls out of set range	
Complete stainless steel construction	Interior and exterior are entirely constructed from stainless steel for lasting durability and easy cleanup	
Glass door	Full display of the interior, with an anti-condensate door frame heater to ensure a clear view	
Forced air cooling	Top-mounted commercial fan ensures rapid temperature recovery	
Automatic defrost with adjustable cycle defrost	Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup	
Self-closing door	Closes to save energy but will remain open when the door is opened at a 90° angle for easier loading	
Open door alarm	Alarm will beep 3 times if the door is left open for 30 seconds, 5 times at 60 seconds, and will sound continuously if the door is open for more than 5 minutes	

ACCUCOLD DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified 770 Garrison Avenue Bronx, NY 10474 USA TEL 718-893-3900 FAX 844-478-8799

info@accucold.com

 $\overline{}$ 

## accucold

### ARG23MLLH Specifications:

Interior Depth

Overview	
Height of Cabinet	83.75" (213 cm)
Width	27.5" (70 cm)
Depth	31.0" (79 cm)
Depth with Handle	32.75" (83 cm)
Depth with door at 90°	56.5" (144 cm)
Capacity	23.0 cu.ft. (651 L)
Defrost Type	Automatic
Door	Glass
Cabinet	Stainless Steel
US Electrical Safety	UL
Canadian Electrical Safety	ULC
Sanitation	ETL-S
Amps	7.5
Voltage/Frequency	115 V AC/60 Hz
Weight	282.0 lbs. (128 kg)
Shipping Weight	292.0 lbs. (132 kg)
Parts & Labor Warranty	2 Years
Compressor Warranty	5 Years
Refrigerator Features	
Door Swing	LHD
Reversible	No
Shelf Type	Wire
Shelf Qty	4
Adjustable Shelves	Yes
Thermostat Type	Digital
Fan Type	Interior
Refrigerant Type	R290a
Refrigerant Amount	2.5oz.
High Side PSI	290.0
Low Side PSI	155.0
Wheel Qty	4
Interior Light	Yes
Temperature Range	2 to 10°C
Dimensions	
Dimensions Interior Height	51.5" (131 cm)

