



About the GE Appliances MSWF water filter cartridge

Water Filter Cartridge

The water filter cartridge is located in the back upper right corner of the refrigerator compartment.

When to replace the filter on models with a replacement indicator light

LCD Models: A pop-up screen will appear on the LCD screen to remind you to replace the water filter. You can check the status of the water filter manually.

Access By: Home > Options > Dispenser Options > Reset Water Filter.

Non-LCD Models: There is a replacement indicator light for the water filter cartridge on the dispenser. This light will turn orange to tell you that you need to replace the filter soon.

The filter cartridge should be replaced when the replacement indicator light turns red or if the flow of water to the dispenser or icemaker decreases.

When to replace the filter on models without a replacement indicator light

The filter cartridge should be replaced every **six months** or earlier if the flow of water to the dispenser or icemaker decreases.

Operating Specifications

- Pressure requirement: 40–120 psi (2.8–8.2 bar), non-shock
- Temperature: 33–100°F (0.6–38°C)
- Flow rate: 0.9 gpm (3.14 lpm)

General Installation/Operation/Maintenance Requirements

- Flush new cartridge at full flow for 4 gallons (about five minutes) to purge trapped air.
- Replace cartridge every six months or sooner if flow becomes too slow.
- Protect from freezing by removing filter cartridge when temperatures are expected to drop below 40°F (4.4°C). Do not install systems in areas where ambient temperatures may go above 100°F or below 40°F. Do not install on a hot water supply.

⚠ WARNING

To reduce the risk associated with choking, do not allow children under 3 years of age to have access to small parts during the installation of this product.

For the maximum benefit of your filtration system, GE Appliances recommends the use of GE-branded filters only. Using GE-branded filters in GE Appliances and Hotpoint® refrigerators provides optimal performance and reliability. GE Appliances filters meet rigorous industry NSF standards for safety and quality that are important for products that are filtering your water. GE Appliances has not qualified non-GE-branded filters for use in GE Appliances and Hotpoint refrigerators and there is no assurance that non-GE-branded filters meet GE Appliances standards for quality, performance and reliability.

If you have questions, or to order additional filter cartridges, visit our website at www.gewaterfilters.com or call GE Appliances Parts and Accessories, 877.959.8688.

Removing/Installing Replacement Filter Cartridge

Removing the Filter Cartridge

If you are replacing the cartridge, first remove the old one by slowly turning it to the left. Pull down gently on the cartridge. A small amount of water may drip down.

CAUTION To reduce the risk associated with property damage due to water leakage, read and follow instructions before installation and use of this system. Installation and use **MUST** comply with all state and local plumbing codes. The disposable filter cartridge should be replaced every six months, at the rated capacity or sooner if a noticeable reduction in flow rate occurs.

Installing the Filter Cartridge



1. On models without a replacement indicator light, apply the month and year sticker to the new cartridge to remind you to replace the filter in **six months**.
2. Fill the replacement cartridge with water from the tap to allow for better flow from the dispenser immediately after installation.
3. Line up the threads on the filter with corresponding threads on the holder. Place the top of the new cartridge up inside the holder. **Do not** push it up into the holder.
4. Slowly turn it to the right until the filter cartridge stops. **DO NOT OVERTIGHTEN**. As you turn the cartridge, it will automatically raise itself into position. The cartridge will move about a 1/2 turn.
5. Run water from the dispenser for 4-1/2 gallons (about five minutes) to clear the system and prevent sputtering.
6. **LCD Models:** Press FILTER REPLACED button to confirm replacement.

Non-LCD Models: Press and hold the RESET WATER FILTER pad (on some models) on the dispenser for three seconds.

NOTE: A newly installed water filter cartridge may cause water to spurt from the dispenser.

Filter bypass plug

To reduce the risk of property damage due to water leakage, you **MUST** use the filter bypass plug when a replacement filter cartridge is not available. The dispenser and the icemaker will not operate without the filter or filter bypass plug.



Performance Data Sheet

SmartWater Filtration System—GE Appliances MSWF Cartridge

This system has been tested and certified in filter model GE Appliances MSWF according to NSF/ANSI Standards 42 and 53 for reduction of the substances listed below. The concentration of the indicated substances in water entering the system was reduced to a concentration less than or equal to the permissible limit for water leaving the system, as specified in NSF/ANSI Standards 42 and 53.* (Safety factors built in for unmetered usage.) The contaminants or other substances removed or reduced by this water treatment system are not necessarily in your water.

MODEL - MSWF Capacity 300 Gallons

Substance Tested for Reduction	Average Influent	NSF specified Challenge Concentration	Avg % Reduction	Average Product Water concentration	Max Permissible Product Water Concentration	NSF Reduction Requirements
Chlorine, Taste and odor	1.96 mg/L	2.0mg/L ± 10%	95.3%	0.09 mg/L	N/A	≥ 50%
Particulate Class I	1,266,667 particles/mL	At least 10,000 particles/mL	98.6%	18167 particles/mL	N/A	≥ 85%
Cyst (Microspheres)	59,098 cysts/L	Minimum 50,000 cysts/L	99.96%	26 cysts/L	N/A	≥99.95%
Asbestos	115 MF/L	107 to 108 fibers/L; fibers greater than 10 µm in length	99.8%	<1 MF/L	N/A	≥99%
Atrazine	0.009 mg/L	0.009mg/L ± 10%	99.5%	.0005 mg/L	0.003 mg/L	N/A
Benzene	0.013 mg/L	0.015 mg/L ± 10% ±	99.0%	0.001 mg/L	0.005 mg/L	N/A
Carbofuran	0.08 mg/L	0.08 mg/L ± 10%	93.3%	.005 mg/L	0.04 mg/L	N/A
Lead 8.5 pH	0.15 mg/L	0.15 mg/L ± 10%	99.6%	0.001 mg/L	0.010 mg/L	N/A
Lead 6.5 pH	0.15 mg/L	0.15 mg/L ± 10%	99.7%	0.004 mg/L	0.010 mg/L	N/A
Lindane	0.002 mg/L	0.002 mg/L ± 10%	94.2%	0.0001 mg/L	0.0002 mg/L	N/A
Mercury 6.5 pH	0.006 mg/L	0.006 mg/L ± 10%	96.8%	0.0002 mg/L	0.002 mg/L	N/A
Mercury 8.5 pH	0.006 mg/L	0.006 mg/L ± 10%	86.7%	0.0008 mg/L	0.002 mg/L	N/A
Toxaphene	0.015 mg/L	0.015 mg/L ± 10%	95.7%	0.006 mg/L	0.003 mg/L	N/A
2, 4-D	0.232 mg/L	0.210 mg/L ± 10%	94.8%	0.01 mg/L	0.07 mg/L	N/A
p-Dichlorobenzene	0.205 mg/L	0.225 mg/L ± 10%	99.95%	<0.01 mg/L	0.075 mg/L	N/A

Application Guidelines/Water Supply Parameters

Service Flow	0.9 gpm (3.4 lpm)
Water Supply	Potable Water

Water Pressure	40-120 psi (2.8-8.2 bar)
Water Temperature	33°F-100°F (0.6°C-38°C)

It is essential that the manufacturer's recommended installation, maintenance and filter replacement requirements be carried out for the product to perform as advertised. See Installation Manual for Warranty information.

Special Notices

- This drinking water system must be maintained according to manufacturer's instructions, including replacement of filter cartridges.

⚠ WARNING

Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used on disinfected water that may contain filterable cysts.

- Check for compliance with the applicable state and local laws and regulations.
- Note that while the testing was performed under standard laboratory conditions, actual performance may vary. Systems must be installed and operated in accordance with manufacturer's recommended procedures and guidelines.

- Installation and use MUST comply with all state and local plumbing codes. Do not install if water pressure exceeds 120 psi. If your water pressure exceeds 80 psi (552 kPa), you should install a pressure-limiting valve. Contact a plumbing professional if you are uncertain how to check your water pressure.
- Do not install where water hammer conditions may occur. If water hammer conditions exist you must install a water hammer arrester. Contact a plumbing professional if you are uncertain how to check for this condition.
- Where a backflow prevention device is installed on a water system, a device for controlling pressure due to thermal expansion must be installed.
- Product certified by IAPMO R&T, which reviews product for material safety, structural integrity, and performance claims on an ongoing basis.



Model MSWF is certified by IAPMO R&T against NSF/ANSI Standard 42 and 53 for the reduction of the claims specified on the Performance Data Sheet.

MSWF Water Filter Cartridge Limited Warranty

Contact GE Appliances at www.geapplianceparts.com, or call 800.GE.CARES.

For the period of	GE Appliances will replace
Thirty Days From the date of the original purchase	Any part of the water filter cartridge which fails due to a defect in materials or workmanship during this limited thirty-day warranty .*

What GE Appliances will not cover:

- Service trips to your home to teach you how to use the product.
- Improper installation.
- Failure of the product if it is abused, misused, used for other than the intended purpose or used commercially.
- Replacement of house fuses or resetting of circuit breakers.
- Replacement of water filter cartridge due to water pressure that is outside the specified operating range or due to excessive sediment in the water supply.
- Damage to the product caused by accident, fire, floods, or acts of God.
- Incidental or consequential damage caused by possible defects with this appliance.

EXCLUSION OF IMPLIED WARRANTIES

Your sole and exclusive remedy is part exchange as provided in this Limited Warranty. Any implied warranties, including the implied warranties of merchantability or fitness for a particular purpose, are limited to six months or the shortest period allowed by law.

This warranty is extended to the original purchaser and any succeeding owner for products purchased for home use within the USA. In Alaska, the warranty excludes the cost of shipping or service calls to your home.

Some states do not allow the exclusion or limitation of incidental or consequential damages. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state. To know what your legal rights are, consult your local or state consumer affairs office or your state's Attorney General.

For Purchases Made In Iowa: This form must be signed and dated by the buyer and seller prior to the consummation of this sale.

This form should be retained on file by the seller for a minimum of two years.

Buyer:

Name _____
 Address _____
 City _____ State _____ Zip _____
 Signature _____ Date _____

Seller:

Name _____
 Address _____
 City _____ State _____ Zip _____
 Signature _____ Date _____

*If your GE Appliances part fails because of a manufacturing defect within thirty days from the date of original purchase for use, we will give you a new or, at our option, a rebuilt part without charge. Return the defective part to the parts supplier from whom it was purchased together with a copy of the "proof of purchase" for the part. If the part is defective and shows no signs of abuse, it will be exchanged. The warranty does not cover the failure of parts which are damaged while in your possession, are abused, or have been installed improperly. It does not cover the cost of returning the part to the supplier from whom it was purchased nor does it cover the cost of labor to remove or install it to diagnose the fault. It does not cover parts used in products in commercial use except in the case of air conditioning equipment. In no event shall GE Appliances be liable for consequential damages. Warrantor: GE Appliances

Staple your receipt here. Proof of the original purchase date is needed to obtain service under the warranty.



GE APPLIANCES

GE is a trademark of the General Electric Company. Manufactured under trademark license.